Chains	
	Reestablishment of the survey executed by Butler Ives, U. S. Deputy Surveyor in 1861 under Contract "A" dated July 15, 1861.
	The Std. cor. of Ts. 11 N., Rs. 21 and 22 E., is an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official field notes of the resurvey of T. 10 N., R. 21 E., executed under this same group.
	From the above std. tp. cor.,
	S. 89° 53' E., on true line, along the S. bdy. of Sec. 31, T. 11 N., R. 22 E., (West half mile.)
	Over rough mountainous land thru heavy timber and medium dense undergrowth.
	Ascend 490 ft. over rocky SW. slope.
38.70	Spur, slopes S. 30° W., continue over gentle E. slope.
39.71	The std. ¼ sec. cor. of sec. 31 which is a pine post, 4 ins. square, 15 ins. long, scribed "S" on one face, firmly set in a large mound of stone. The position of this corner is verified by the two original bearing trees.
	At point for cor.,
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original corner post deposited at the base, for std. ¼ sec. cor., with brass cap mkd.
	S C ¼ S 31 1940
	from which
	Original bearing trees: A pinon pine, 6 ins. diam., bears N. 13½° E., 44 lks. dist., with scribe marks plainly visible thru the partially overgrown blazed surface. A pinon pine, 14 ins. diam., bears S. 17½° E., 53 lks. dist., with scribe marks plainly visible thru the partially overgrown blazed surface. New bearing trees: A pinon pine, 9 ins. diam., bears N. 40½° E., 27 lks. dist., mkd. SC ¼ S 31 BT. A pinon pine, 10 ins. diam., bears N. 19½° W., 81 lks. dist., mkd. SC ¼ S31 BT.
	Thence
	N. 89° 53' E., along the S. bdy. of Sec. 31, (East half mile.)
	Over rough mountainous land thru medium dense timber and medium heavy tall undergrowth.
	Descend gentle SE. slope.
5.00	Head of broad shallow draw, drains S., asc. 40 ft. over gentle W. slope.
15.00	Ridge, bears N. and S., desc. 460 ft. over abrupt, rocky E. slope.
36.40	Short draw, drains NE., asc. 20 ft. over NW. slope.
39.95	The std. cor. of secs. 31 and 32 which is a weathered cedar post, 4 ins. square, 20 ins. long, securely set in a large mound of stone,