

DEPENDENT RESURVEY OF THE SUBDIVISION OF T. 10 N., R. 22 E.

Chains

A pinon pine, 7 ins. diam., bears S. $34\frac{3}{4}^{\circ}$ W., 62 lks. dist., mkd. T10N R22E S6 CC BT.

From this closing cor.,

The Std. cor. of secs. 31 and 32 bears N. $89^{\circ} 53'$ E., 11.48 chs. distant.

Land, mountainous.

Soil, shallow coarse rocky loam, 3rd to 4th rate.

Undergrowth, sagebrush, buck bursh.

Timber, pinon pine, juniper.

Grazing, good.

METES AND BOUNDS SURVEY OF PRIVATE CLAIMS IN T. 10 N., R. 22 E.

TRACT No. 37

Desert Entry, No. 80686, to David G. Corbette; application dated May 1, 1877, patent dated February 25, 1879 for the following lands; Sec. 29, $E\frac{1}{2}SE\frac{1}{4}$ and $SW\frac{1}{4}SE\frac{1}{4}$. Sec. 32, $E\frac{1}{2}NW\frac{1}{4}$, $W\frac{1}{2}NE\frac{1}{4}$, $NW\frac{1}{4}SE\frac{1}{4}$ and Lots 3, 4 and 5 totalling 401.87 acres as shown upon the official plat of T. 10 N., R. 22 E., M.D.Mer., Nevada approved August 7, 1877.

Topaz Lake Reservoir, a dry pond at the time of the original survey, has been artificially enlarged and now covers all or portions of each of the foregoing subdivisions. The $E\frac{1}{2}SE\frac{1}{4}$ and $SW\frac{1}{4}SE\frac{1}{4}$ of Sec. 29 and the $W\frac{1}{2}NE\frac{1}{4}$ and the $NE\frac{1}{4}NW\frac{1}{4}$ of Sec. 32 are conformable to the lines of the resurvey. The $SE\frac{1}{4}NW\frac{1}{4}$, $NW\frac{1}{4}SE\frac{1}{4}$ and Lots 3, 4 and 5 of Sec. 32 with a total area of 161.87 acres are either invaded by or lie entirely south of the present California-Nevada state boundary and are surveyed as one unit which is designated Tract No. 37. A Monument, marking the NW 1/16 section cor. of sec. 32, is accepted as initial cor. for the survey of Tract No. 37 and alignment control along line 1-2 was determined by a projection of the line from the W. 1/16 sec. cor. of secs. 29 and 32, which is in harmony with the remains of an old fence line. The remaining boundary lines are run to conform to a theoretical subdivision of sec. 32. Angle points Nos. 3 to 7 incl., at computed positions, fall at inaccessible positions in the reservoir and were not monumented.

The NW 1/16 sec. cor. of sec. 32, which was marked by a rough surfaced pine stake, 2 ft. long, 3 ins. square, with "SE cor. $NW\frac{1}{4}NW\frac{1}{4}$ " in faint but distinct marks on one face, and set in a large mound of stone, now becomes angle point cor. 1/37 and 3/38 and is monumented as follows:

At point for cor., in center of mound,

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, and in a large circle of stones, for angle point cor. 1/37 and 3/38, with brass cap mkd.

T10N	R22E
AP3	S 32
TR 38	NW 1/16
	AP1
	TR 37

1945

Thence

From Cor. No. 1 of Tract No. 37