	6	Dependent Resurvey of the N. Bdy. of T. 7 N., R. 45 E.
120 120 120	Chains 78.94	Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance. No trace of the original cor. was found.
		This cor. is now altered and refers and stands for the cor. of secs. 5 and 6, T. 7 N., R. 45 E. only.
		At the proportionate point.
		Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.
A CONTRACTOR OF THE PARTY OF TH		T 8N RIJIZE  S 36  S6 S5  T 7N R45E
CO C - ST - ST	1	1939
		Raise a mound of stone, 2 ft. base, $l_{\overline{z}}$ ft. high, S. of corner.
	8	This cor. is situated on top of spur, projects S. 25° E.
		Land, rolling mountainous. Soil, sandy, gravelly and rocky; 3rd rate. No timber; undergrowth, sagebrush and shadscale. Grazing, fair.
		N. 75° 31' W., along the N. bdy. of sec. 6.
		Over rolling mountainous land, through dense undergrowth, descend 10 ft.
	5•90	Wash, 15 lks. wide, 3 ft. deep, course S. 30° E.; asc. 10 ft.
	19.10	Wash, 15 lks. wide, with sloping banks 4 ft. high, course S. 35° E.; asc. 70 ft.
	38.82	Point for the \$\frac{1}{4}\$ sec. cor. of sec. 36, T. 8 N., R. \$\frac{1}{44\frac{1}{2}}\$ E., which is \$40.00\$ chs. in departure from the SE. cor. of T. 8 N., R. \$\frac{1}{44\frac{1}{2}}\$E.
		At the point for cor.
	<i>8</i>	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	180 J	½ S 36
		1939
,	6	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	39.47	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance. All evidence of the original $\frac{1}{4}$ sec. cor. has disappeared.
	_	This cor. is now altered and refers and stands for the $\frac{1}{4}$

sec. cor. of sec. 6, T. 7 N., R. 45 E. only.

At the cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.