

Survey of the East Boundary of T.8 N., R.44 E., M.D.M., Nevada.

Chains

These surveys were made with General Land Office instruments conforming to the standard specifications of this bureau. For details refer to the field notes of the surveys and resurveys of the boundaries of T.8 N., R.45 E. executed under this Group.

The East boundary of T.8 N., R.44 E., was surveyed on a cardinal line, North, from the corner of Ts.8 N., Rs.44 and 44½ E., identical with the restored corner of Ts.7 N., Rs.44 and 45 E. Corners referring to this township and range only were established at regular intervals of 40 and 80 chains, to the point of intersection with the North boundary of the Tp.

North, along the E. bdy. of sec. 36.

Over mountainous land, through scattered timber and dense undergrowth; asc. 35 ft.

- 5.00 Top of spur, slopes E., desc. 45 ft.
 8.15 Wash, course E.; asc. 100 ft.
 13.20 Top of spur, slopes S.70°E.; asc. 40 ft.
 18.20 Top of spur, slopes N.80°E.; desc. 100 ft.
 22.40 Wash, course E.; asc. 45 ft.
 25.60 Top of spur, projects S.80°E.; desc. 40 ft.
 29.00 Wash, course S.80°E.; asc. 200 ft.
 40.00 Point for ¼ sec. cor. of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with a porphyry rock, 6x6x4 ins., mkd. with a cross (X), deposited at the base, and in a mound of stone to top, with brass cap mkd.

¼ S36

1939

No suitable accessories are available.

Asc. 45 ft.

- 43.10 Top of spur, and W. end of knoll, projects N.40°E., and S.50°E., from W.; desc. 135 ft.
 48.70 Wash, course N.80°E.; asc. 60 ft.
 53.80 Top of spur, slopes N.30°E.; desc. 170 ft.
 59.10 Ravine, course E.; asc. 360 ft.
 80.00 Point for the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 25 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd.