

East Boundary of T.8 N., R.44 E., M.D.M.

Chains

North, along the E. bdy. of sec. 1.

Over mountainous land, through scattered timber and dense undergrowth. Asc. 10 ft.

5.00 Point of spur, slopes SW.; desc. 20 ft.

11.10 Ravine, course SW.; asc. 340 ft. over SE. slope.

11.20 Road, unimproved, bears N.50°E. and S.30°W.

38.30 Top of spur, projects S.70°E.; desc. 5 ft.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ Sl

1939

from which

A pinon pine, 5 ins. diam., bears S.61 $\frac{1}{2}$ °W., 111 lks. dist., mkd. $\frac{1}{4}$ Sl BTA pinon pine, 8 ins. diam., bears N.83°W., 195 lks., dist., mkd. $\frac{1}{4}$ Sl BT

Desc. 95 ft. over NE. slope.

48.60 Wash, course E.; asc. 60 ft.

51.50 Top of spur, slopes E.; desc. 30 ft.

53.90 Wash, course E.; asc. 40 ft.

56.50 Top of spur, slopes E.; desc. 110 ft.

63.60 Wash, course N.80°E.; asc. 20 ft.

67.10 Top of spur, slopes E.; desc. 90 ft.

75.80 Wash, course E.; asc. 30 ft.

80.00 Point for the corner of lots 1 and 8, of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, to bedrock, with a porphyry rock 6x6x5 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, with brass cap mkd.

T8N
1
S 1 $\frac{1}{8}$
R44E

1939

from which

A pinon pine, 8 ins. diam., bears S.40 $\frac{1}{2}$ °W., 132 lks. dist., mkd. T8N R44E S1 L8 BT