

Chains

From the cor. of Ts.8 and 9 N., Rs.44½ and 45 E., marked by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the 1939 survey, executed under this Group.

West, along the N. bdy. of sec. 1.

Over mountainous land, through scattered timber and dense undergrowth; asc. 130 ft. over rocky NE. slope.

- 4.60 Top of rocky spur, projects SE.; desc. 30 ft.
- 9.30 Drain, course S.; asc. 60 ft.
- 14.50 Point of spur, projects S.; desc. 70 ft.
- 22.20 Ravine, course SE.; asc. 330 ft. over broken, rocky NE. slope.
- 39.70 Edge of rimrock, bears N.20°E. and S.20°W.; asc.
- 40.00 Point for ¼ sec. cor. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, with a granite stone 6x6x5 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, with brass cap mkd.

¼ S 1

1939

from which

A pinon pine, 8 ins. diam., bears S.52°E., 14 lks. dist., mkd. ¼ S1 BT


A pinon pine, 6 ins. diam., bears S.55½°W., 24 lks. dist., mkd. ¼ S1 BT

Asc. 25 ft. over SE. slope.

- 43.70 Top of ridge, bears N.20°W., and S.10°E.; desc. 60 ft.
- 52.90 Head of ravine, course S.20°E.; asc. 25 ft.
- 56.60 Top of spur, projects S.20°W.; desc. 240 ft.
- 64.40 Wash, course SW.; asc. 30 ft.
- 66.80 Top of spur, slopes SW.; desc. 110 ft.
- 76.57 Intersect the E. bdy. of T.8 N., R.44 E.

Point for the closing cor. of T.8 N., R.44½ E.

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground, to bedrock, with a limestone 7x6x4 ins., mkd. with a cross (X) deposited at the base, and in a mound of stone to top, with brass cap mkd.



1939