

## Dependent Resurvey of the North Boundary of T. 7 N., R. 44 E.

Chains

N. 89° 11' W., along the N. bdy. of sec. 6.

Note: This line crosses "Cherokee" lode, Survey No. 1657 and "Wyoming" lode, Survey No. 1658, but no remaining evidence of the corner monuments of these mining claims could be found.

Over mountainous land, through scattering timber and dense undergrowth; asc. 135 ft. over E. slope.

- 4.90 Top of ridge, bears S. 30° E. 5.00 chs. to saddle, from N. 1.00 ch. to knoll; desc. 145 ft. over rocky W. slope.
- 10.70 Ravine, course S. 10° W. from N. 10° E. 2.00 chs. to head; asc. 180 ft. over E. and SE. slopes.
- 17.50 Top of rugged and sharp reef rocky spur, projects S.; from this point Cote Springs, bears S. 0° 28' E.; desc. 160 ft. over series of granite outcroppings facing SW.
- 25.30 Rocky ravine, course S. 20° E. for 2.00 chs., thence winds S.; asc. 245 ft. over series of abrupt out-croppings facing SE., S., and SW.
- 31.00 Edge of rimrock, bears N. and S.; asc. 25 ft. over same.
- 32.40 Top of ascent; desc. 85 ft. over SW. slope.
- 34.70 Head of wash, course SE.; asc. 125 ft. over SE. slope.
- 39.67 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31, T. 8 N., R. 44 E. only, at 40.00 chs. westing from the cor. of secs. 31 and 32.
- Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with brass cap mkd.
- $\frac{1}{4}$  S 31  
1939
- Deposit a porphyry stone, 6x6x4 ins., mkd. X, at the base, and raise a supporting mound of stone, 2 $\frac{1}{2}$  ft. base, 20 ins. high, around the iron post.
- from which
- A pinon, 7 ins. diam., bears N. 74 $\frac{3}{4}$ ° E., 103 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.
- A pinon, 5 ins. diam., bears N. 20 $\frac{1}{2}$ ° W., 38 lks. dist., mkd.  $\frac{1}{4}$  S31 BT.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at record distance of 40.00 chs. westing from the cor. of secs. 5 and 6, T. 7 N., R. 44 E. There is no remaining evidence of the original corner. As this cor. will no longer serve for sec. 31, it is now reestablished to refer to sec. 6 only.
- Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with brass cap mkd.

$\frac{1}{4}$  S 6  
1939

Deposit a porphyry stone, 6x6x4 ins., mkd. X, at the base, and raise a supporting mound of stone, 2 ft. base, 16 ins. high, around the iron post.