## Survey of the Subdivision of T. 8 N., R. 44 E.

Chains	
	Note: The south boundary of the township, being out of limits for bearing, is not suitable as a governing line for control of the location of subdivisional lines. Accordingly, a sectional correction line is initiated at the corner of sections 25 and 36 on the E. bdy. of the township and projected on a bearing of West, across the township to its west boundary.
	Beginning the subdivisional survey at the cor. of secs. 35 and 36, on the S. bdy. of the township.
	N. 0° 01' W., bet. secs. 35 and 36.
c	Asc. gradually over broken rolling mountainous land, through scattering timber and undergrowth; along SE. slope.
6.80	Wash, 20 lks. wide, course S. 35° E. from NW.; asc. 125 ft. over S. slope.
10.00	Flat spur, slopes SE.; thence along E. slope.
18.60	Wash, course S. 60° E.; leave rolling and enter mountainous land, bears NW. and SE.; asc. 135 ft. over S. slope.
28.70	Top of granite outcropping on spur, projects SW.; asc. 15 ft. along W. slope.
29.90	Top of ridge, bears N. 70° W. and S. 70° E.; desc. 90 ft. over N. slope.
34.50	Head of ravine, course S. 80° E.; asc. 40 ft. over S. slope.
36.10	Slope changes; asc. 40 ft. along general W. slope.
39.76	Point for the 2 sec. cor. of secs. 35 and 36, at 40.00 chs. southing from sectional correction line.
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with brass cap mkd.
	1
	\$35   \$36 1939
	Deposit a granite stone, 6x5x4 ins., mkd. X, at the base, and raise a supporting mound of stone, 2 ft. base, 1½ ft. high, around the iron post.
	from which
	A juniper, 12 ins. diam., bears N. 87° E., 53 lks. dist., mkd. ½ S36 BT.
	A pinon, 8 ins. diam., bears S. 55° W., 128 1ks. dist., mkd. ½ S35 BT.
47.70	Head of ravine, course S. 10° W.; asc. 160 ft. along W. slope.
51.40	Saddle in divide ridge, ridge bears E. and W.; desc. 100 ft. over N. slope.
56.10	Ravine, course NE. from S. 60° W.; asc. 20 ft. over SE. slope.
60.90	Spur, slopes E.; desc. 120 ft. over NE. slope.
68.60	Ravine, channel 1 ch. wide, course S. 10° E. for about 5.00 chs., thence S. 60° E. from N. 70° W.; asc. 160 ft. over broken SW. slope.