

5TH STANDARD PARALLEL SOUTH  
thru R. 70 E.

Chains

39.50

Spur, projects NE.; desc. 850 ft. over rocky SE. slope changing to E. slope.

40.00

N. 15 lks. from the tangent.

Set an iron post, 3 ft. long, 1 in. diam., 2 ins. in the ground, to bedrock, with a limestone 6x4x2 ins., mkd. X, deposited at base, and in a mound of stone to top, for standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
S 35

$\frac{1}{4}$

S 2

1939

80.00

N. 18 lks. from the tangent.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard corner of secs. 1, 2, 35 and 36, with brass cap mkd.

S C  
T20S R70E  
S 35 S 36

S 2 S 1

T21S

1939

raise a mound  
of stone, 2 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

Land, mountainous.

Soil, rocky; 4th rate.

No timber; undergrowth, black brush, creosote, cactus and mountain rush.

Grazing, poor.

East, bet. secs. 1 and 36, on tangent line,

Desc. slightly over E. slope.

0.50

Draw, drains irregularly SE.; asc. 60 ft. over SW. slope.

5.00

Spur, slopes S. 30° E., 100 ft. over rolling land, draining generally SE.

16.00

Spur, projects irregularly SE., desc. 450 ft. over rolling land draining E.

40.00

N. 22 lks. from the tangent.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
S 36  
 $\frac{1}{4}$  S 1

1939

raise a mound  
of stone, 2 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor.

61.80

Draw, drains SE.; over rolling land drains generally SE., desc. 70 ft.

80.00

N. 26 lks. from the tangent.