

445

Dependent Resurvey, Portion of the East Boundary, T. 19 N., R. 64 E.

Chains

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 35 \\ S 2 \\ 1943 \end{array}$$
Deposit the old corner stone at base of the iron post, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Land, mountainous.

Soil, gravelly and rocky.

Timber, juniper and pinon; undergrowth, sagebrush.

Dependent Resurvey, Portion of the Subdivision, T. 19 N., R. 65 E.

Reestablishment of the Survey Executed By
Monroe and Bateman, Deputy Surveyors, in 1872.

Beginning at the corner of secs. 4, 5, 32 and 33, on the S. bdy. of the township, monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of a portion of the N. bdy. of T. 18 N., R. 65 E., executed concurrently under Group 190.

N. $0^{\circ} 07'$ E., bet. secs. 32 and 33.

Asc. slightly over mountainous land, through timber and undergrowth.

1.40 Spur, projects W.; desc. 150 ft. over N. slope.

7.20 Pipe line, bears E. and W.

8.00 Dry channel of Bird Creek, 5 ft. wide, 3 ft. deep, course S. 85° W.; asc. 80 ft. over S. slope.

8.80 Graded road, bears E. and W.

9.70 Pipe line, bears E. and W.

17.20 Junction of unimproved road, bears S. 75° E., N. 80° E. and W.

19.00 Spur, slopes W.; desc. 50 ft. over NW. slope.

23.70 Ravine, course W.; asc. 50 ft. over SW. slope.

27.00 Spur, slopes W.; desc. 40 ft. over NW. slope.

31.00 Ravine, course N. 75° W.; asc. 50 ft. over SW. slope.36.10 Spur, slopes N. 70° W.; desc. 50 ft. over NW. slope.40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S32 \quad | \quad S33 \\ 1943 \end{array}$$