

Subdivision of T. 40 N., R. 35 E.

562

Chains

$$\frac{1}{4}$$

S 4		S 3
1940		

No suitable accessory.

79.26 Intersect the 8th standard parallel N.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the closing cor. of secs. 3 and 4, with brass cap mkd.

T 41 N R 35 E		
S 33		

S 4		S 3
CC		
T 40 N R 35 E		
1940		

No suitable accessory.

From this point, the standard cor. of secs. 33 and 34, bears N. 88° 46' E., 6.93 chs. dist.

Land, nearly level.
Soil, sandy, alkaline clay, ed rate.
No timber; undergrowth, sagebrush and greasewood.
Grazing, poor.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.

N. 0° 03' W., bet. secs. 32 and 33.

Desc. 50 ft. over rolling land, along a W. slope, thru scattering undergrowth.

- 3.20 Draw, drains N. 40° W.
- 14.00 Draw, drains N. 80° W.
- 37.30 Road, bears N. 60° W. and S. 60° E.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

S 32		S 33
1940		

No suitable accessory.

- 45.10 Draw, drains N. 80° W.
- 47.30 Power line from Austin Well to Austin Mill, bears N. 80° W. and S. 80° E.
- 47.60 Road, bears N. 80° W. and S. 80° E.
- 50.40 Draw, drains S. 70° W.
- 50.90 Road, bears E. and W.
- 66.30 Road, bears E. and W.