

Subdivision of T. 39 N., R. 36 E.

603

Chains	
	scattering undergrowth.
6.10	Top of ascent, bears N. and S.; desc. 10 ft. abruptly.
7.80	Draw, drains S. 60° E.; asc. 130 ft. over a NE. slope.
16.30	Spur, slopes S. 20° E.; desc. 80 ft. over a SW. slope.
29.10	Draw, drains SE.; asc. 150 ft. over an E. slope.
39.50	Spur, slopes S. 30° E.; desc. 30 ft. over broken land.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, with a granite stone, 6x4x2 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} S \ 30 \\ \hline S \ 31 \\ 1940 \end{array}$
	No suitable accessory.
51.10	Draw, drains SE.; asc. 270 ft. over a SE. slope.
65.30	Spur, slopes S.; desc. 70 ft. over a SW. slope.
73.30	Draw, drains S. 30° E.; asc. 170 ft. over a SE. slope.
80.30	Intersect the Humboldt River Guide Meridian.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a granite stone, 7x5x3 ins., mkd. with a cross (X), deposited at base, for the closing cor. of secs. 30 and 31, with brass cap mkd.
	$\begin{array}{r l} T39N & T39N \\ R35E & S30 \\ S25 & S31 \\ & R36E \end{array} \quad CC$
	1940
	No suitable accessory.
	From this point the cor. of secs. 25 and 36, T. 39 N., R. 35 E., bears S. 6.08 chs. dist.
	Land, rolling mountainous. Soil, sandy, alkaline clay; 3d rate. No timber; undergrowth, sagebrush and shadscale. Grazing, fair.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0° 03' W., bet. secs. 29 and 30.
	Asc. 40 ft. over rolling mountainous land, on a SE. slope, thru scattering undergrowth.
8.40	Top of ascent bears NW and SE.; desc. 70 ft. along an E. slope.
31.80	Draw, drains N. 80° E.; asc. 50 ft. over a S. slope.
36.50	Spur, slopes E.; desc. 90 ft. along an E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,