

## Subdivision of T. 39 N., R. 36 E.

Chains

77.00

Rocky spur, slopes E.; desc. 50 ft. over a W. slope.

80.01

Intersect the Humboldt River Guide Meridian.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bedrock, with a basalt stone, 6x5x3 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top, for the closing cor. of secs. 7 and 18, with brass cap mkd.

T39N	T39N	
R35E	S 7	
	S18	CC
S12	R36E	

1940

From this point the cor. of secs. 12 and 13, T. 39 N., R. 35 E., bears South, 6.20 chs. dist.

Land, rolling mountainous.

Soil, rocky, sandy clay; 3d rate.

No timber; undergrowth, sagebrush and shadscale.

Grazing, fair.

---

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 03' W., bet. secs. 7 and 8.

Desc. 280 ft. over rolling mountainous land, along an E. slope, thru scattering undergrowth.

14.20

Draw, drains N. 80° E.; asc. 60 ft. over a S. slope.

21.10

Spur, slopes S. 70° E.; desc. 80 ft. along a NE. slope.

28.00

Draw, drains SE.; asc. 300 ft. over a S. slope.

34.80

Draw, drains S. 25° W.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a basalt stone 6x4x4 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

	$\frac{1}{4}$	
S7	S8	
	1940	

45.60

Spur, slopes S. 60° E.; desc. 70 ft. along an E. slope.

54.90

Draw, drains SE.; asc. 60 ft. over a SE. slope.

62.00

Draw, drains S. 70° E.; asc. 110 ft. along an E. slope.

71.80

Draw, drains E.; over broken ground.

73.40

Draw, drains SE.; asc. 150 ft. over a S. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, upon a cross (X) on bedrock, and in a mound of stone to top, for the cor. of secs. 5, 6, 7 and 8, with brass cap mkd.

T39N	R36E	
S 6	S 5	
S 7	S 8	
	1940	