

Subdivision of T. 39 N., R. 36 E.

Chains

No suitable accessory.

41.00 Draw, drains S.; asc. 200 ft. over an E. slope.

60.00 Spur, slopes S.; desc. 80 ft. over a SW. slope.

67.90 Draw, drains SE.; asc. 250 ft. over a NE. slope.

79.97 Intersect the Humboldt River Guide Meridian.

Set an iron post, 3 ft. long, 2 ins. diam., 2⁴ ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap mkd.

T39N	T39N	
R35E	S 6	
		CC
	S 7	
S 1	R36E	
		1940

raise a mound
of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

From this point, the cor. of secs. 1 and 12, T. 39 N., R. 35 E., bears South 6.14 chs. dist.

Land, rolling mountainous.

Soil, rocky, sandy alkaline clay; 3d rate.

No timber; undergrowth, sagebrush and shadscale.

Grazing, fair.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 07' E., on a random line bet. secs. 5 and 6.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

73.78 Intersect the N. bdy. of the Tp., 9 lks. E. of the cor. of secs. 5, 6, 31 and 32, heretofore described.

Thence

S. 0° 03' W., on true line bet. secs. 5 and 6.

Desc. 30 ft. over rolling mountainous land, on a S. slope, thru scattering undergrowth.

2.10 Draw, drains E.; asc. 310 ft. over a N. slope.

5.30 Road, bears E. and W.

14.90 Road, bears N. 60° E. and W.

17.60 Road, bears N. 60° W. and S. 60° E.

18.00 Spur, slopes E.; desc. 170 ft. over a S. slope.

26.00 Draw, drains S. 60° E.; asc. 100 ft. over a N. slope.

31.80 Spur, slopes S. 60° E., 15.00 chs. to point; desc. 140 ft. over a S. slope.

33.78 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock, with a basalt stone 7x5x3 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

	$\frac{1}{4}$	
S 6		S 5
		1940