R. 37 E., therefore, I erase the markings upon the cor. monument referring to Tps. 39 and 40 N., R. 36 E. Land, nearly level. Soil, sandy, alkaline clay, 3d rate. No timber; undergrowth, sagebrush. Grazing, poor. IMDEPENDENT RESURVEY OF HUMBOLDT RIVER GUIDE MERIDIAN THRU T. 39 N. Superseding the survey executed by O. A. Palmer, U. S. Deputy Surveyor, 1866. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 367 hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a N. slope. 20.30 Spur, slopes E.; desc. 100 ft. along an E. slope. Draw, drains N. 80° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 2 sec. cor. of sec. 36, with brass cap mkd. 14.90 Draw, drains S. 60° E.; asc. 110 ft. over a S. slope. Spur, slopes SE.; desc. 10 ft. over a S. slope. Spur, slopes SE.; desc. 10 ft. over a S. slope. Spur, slopes SE.; desc. 10 ft. over a S. slope. Spur, slopes SE.; desc. 10 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a grante stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd.		
The cor. of Tps. 39 and ho H., Rs. 36 and 37 E.; an iron post, 3 instian., 12 ins. above ground, mkd. and witnessed as described in the official record. This sor, will hereafter refer to Tps. 39 and ho K., R. 37 E., therefore, I cruse the markings upon the cor. monument referring to Tps. 39 and ho N., R. 36 E. Land, nearly level. Soil, sandy, alkaline clay, 3d rate. Not imber; undergrowth, sagebrush. Grazing, poor. INDEPENDENT RESURVAY OF HUMBCLDT RIVER GUIDE MERIDIAN THRU T. 39 N. Superseding the survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 36 thereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains NE.; desc. 100 ft. over a N. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. 10.00 of stone, 2 ft. base, 12 ft. high, W. of cor. Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. Spur,	Chains	
diam., 12 ins. above ground, mkd. and witnessed as described in the official record. This core. will hereafter refer to Tps. 39 and 10 N., R. 37 E., therefore, I erase the markings upon the cor. monument referring to Tps. 39 and 10 N., R. 36 E. Land, nearly level. Soil, sandy, alkaline clay, 3d rate. No timber; undergrowth, sagebrush. Grazing, poor. IMDEFENDENT RESURVEY OF HUMBOLDT RIVER GUIDE MERIDIAN THRU T. 39 N. Superseding the survey executed by O. A. Palmer, U. S. Deputy Surveyor, 1866. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Re. 35 and 367 hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains NE.; desc. 100 ft. over a N. slope. Draw, drains NE.; desc. 100 ft. over a N. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. 39-10 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ½ sec. cor. of sec. 36, with brass cap mkd. 4 S 36 1940 of stone, 2 ft. base, 1½ ft. high, W. of cor. Draw, drains S. 60° E.; asc. 110 ft. over a S. slope. Spur, slopes SE.; desc. h0 ft. over a S. slope. Spur, slopes SE.; desc. h0 ft. over a S. slope. Spur, slopes SE.; desc. h0 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a grante stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 35, with brass cap mkd.	70.63	
Soil, sandy, alkaline clay, 3d rate. No timber; undergrowth, sagebrush. Grazing, poor. IEDEPENDENT RESURVEY OF HUMBOLDT RIVER GUIDE MERIDIAN THRU T. 39 N. Superseding the survey executed by O. A. Palmer, U. S. Deputy Surveyor, 1868. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 365 hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains NE.; desc. 100 ft. over a N. slope. 28.50 Draw, drains NE.; desc. 140 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. 10.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \$\frac{1}{2}\$ sec. cor. of sec. 36, with brass cap mkd. \$\frac{1}{2}\$ S 36\$ \$\frac{1}{2}\$ 1940 of stone, 2 ft. base, 1\frac{1}{2}\$ ft. high, W. of cor. Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope.		diam., 12 ins. above ground, mkd. and witnessed as described in the official record. This cor. will hereafter refer to Tps. 39 and 40 N., R. 37 E., therefore, I erase the markings upon the cor. monument
Superseding the survey executed by O. A. Falmer, U. S. Deputy Surveyor, 1866. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 36, hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a N. slope. Spur, slopes E.; desc. 100 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. 10.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \$\frac{1}{2}\$ sec. cor. of sec. 36, with brass cap mkd. \$\frac{1}{2}\$ \$36 \\		Soil, sandy, alkaline clay, 3d rate. No timber; undergrowth, sagebrush.
Surveyor, 1868. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 36 hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a S. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \$\frac{1}{4}\$ sec. cor. of sec. 36, with brass cap mkd. \$\frac{1}{4}\$ \$36\$ \$\frac{1}{4}\$ \$400 Traw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 140 ft. over a S. slope. Tr.70 Draw, drains S. 60° E.; asc. 110 ft. over a S. slope. Spur, slopes SE.; desc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Sot an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (\frac{1}{4}\), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N \$\frac{825}{836}\$ \$\frac{1358}{835}\$ \$\frac{1358}{835}\$ \$\frac{1358}{835}\$		INDEPENDENT RESURVEY OF HUMBOLDT RIVER GUIDE MERIDIAN THRU T. 39 N.
Surveyor, 1868. I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 36 hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a S. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \$\frac{1}{4}\$ sec. cor. of sec. 36, with brass cap mkd. \$\frac{1}{4}\$ \$36\$ \$\frac{1}{4}\$ \$400 Traw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 140 ft. over a S. slope. Tr.70 Draw, drains S. 60° E.; asc. 110 ft. over a S. slope. Spur, slopes SE.; desc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Sot an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (\frac{1}{4}\), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N \$\frac{825}{836}\$ \$\frac{1358}{835}\$ \$\frac{1358}{835}\$ \$\frac{1358}{835}\$		
Rs. 35 and 36; hereinbefore described. North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E. Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a S. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains NE.; desc. 140 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{2}\) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{2}\) S 36 \[\frac{1}{2}\) 1940 \[\text{raise a mound} \] of stone, 2 ft. base, 1\frac{1}{2}\) ft. high, W. of cor. Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N \[\frac{325}{325}\] \[\frac{325}{336}\] \[\frac{325}{336}\] \[\frac{325}{335}\]		
Desc. 100 ft. over mountainous land, on a NE. slope, thru dense undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. Draw, drains E.; asc. 60 ft. over a N. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains NE.; desc. 140 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{4} \) S 36 \[\frac{1}{4} \] S 36 \[\frac{1}{4} \) S 36 \[\frac{1}{4} \) S 36 \[\frac{1}{4} \]		I commence this survey at the reestablished cor. of Tps. 38 and 39 N., Rs. 35 and 36^{E} , hereinbefore described.
undergrowth. 6.90 Draw, drains NE.; desc. 110 ft. over a broken N. slope. 14.90 Draw, drains E.; asc. 60 ft. over a S. slope. 20.30 Spur, slopes E.; desc. 100 ft. over a N. slope. 28.50 Draw, drains NE.; desc. 140 ft. along an E. slope. 36.30 Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{2}\) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{4}\) S 36 \[\frac{1}{4}\) S 36 \[\frac{1}{4}\) S 36 \[\frac{1}{2}\) ft. high, W. of cor. \[\frac{1}{4}\) S 36 \[\frac{1}{2}\) Spur, slopes SE.; desc. 40 ft. over a S. slope. \[\frac{1}{2}\) Spur, slopes SE.; desc. 40 ft. over a NE. slope. \[\frac{1}{2}\) Spur, slopes SE.; over broken land. \[\frac{1}{2}\) Set an iron post, 3 ft. long, 2 ins. dism., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (\hat{1}\), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. \[\frac{1}{2}\) Spir \frac{1}{2}\) T39N \[\frac{1}{2}\) T39E \[\frac{1}{2}\) R36E \[\frac{2}{2}\) R36E \[\frac{2}{2}\) R36E \[\frac{2}{2}\) R36E \[\frac{2}{2}\) R36E		North, along the E. bdy. of sec. 36, T. 39 N., R. 35 E.
Draw, drains E.; asc. 60 ft. over a S. slope. Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains NE.; desc. 140 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ½ sec. cor. of sec. 36, with brass cap mkd. 2 S 36 1940 raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N R36E S36 R35E S31		
Spur, slopes E.; desc. 100 ft. over a N. slope. Draw, drains NE.; desc. 140 ft. along an E. slope. Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. Draw, drains N. 80° E.; over broken land. Draw, drains N. 80° E.; over broken land. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \$\frac{1}{4}\$ S 36 1940 Draw, drains SE.; asc. 100 ft. over a S. slope. Draw, drains SE.; desc. 40 ft. over a S. slope. Tray, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. Tayn S25 S36 R35E S31	6.90	Draw, drains NE.; desc. 110 ft. over a broken N. slope.
Draw, drains NE.; desc. 140 ft. along an E. slope. 36.30 Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. 39.40 Draw, drains N. 80° E.; over broken land. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{2} \) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{2} \) S 36 \\ \text{1940} \] of stone, 2 ft. base, 1\(\frac{1}{2}\) ft. high, W. of cor. 144.90 Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd.	14.90	Draw, drains E.; asc. 60 ft. over a S. slope.
Draw, drains N. 70° E.; desc. 60 ft. over a N. slope. 39.40 Draw, drains N. 80° E.; over broken land. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ½ sec. cor. of sec. 36, with brass cap mkd. 14 S 36 1940 raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd.	20.30	Spur, slopes E.; desc. 100 ft. over a N. slope.
Draw, drains N. 80° E.; over broken land. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{4} \) S 36 \] \[\frac{1}{4} \) S 36 \] \[\frac{1}{2} \) Taise a mound of stone, 2 ft. base, 1\(\frac{1}{2} \) ft. high, W. of cor. \[\frac{1}{4} \) S 36 \] \[\frac{1}{2} \) Taw, drains SE.; asc. 100 ft. over a S. slope. \[\frac{1}{2} \) Spur, slopes SE.; desc. 40 ft. over a NE. slope. \[\frac{1}{2} \) Tow, drains S. 60° E.; asc. 140 ft. over a S. slope. \[\frac{1}{2} \) Spur, slopes SE.; over broken land. \[\frac{1}{2} \) Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. \[\frac{1}{2} \) T39N \[\frac{3}{2} \) S36 \[\frac{3}{2} \) R35E \[\frac{3}{2} \) S31	28.50	Draw, drains NE.; desc. 140 ft. along an E. slope.
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{4} \) S 36 \\	36.30	Draw, drains N. 70° E.; desc. 60 ft. over a N. slope.
for \(\frac{1}{4} \) sec. cor. of sec. 36, with brass cap mkd. \[\frac{1}{4} \) S 36 \] \[1940 \] \[\text{raise a mound} \] \[\text{of stone, 2 ft. base, 1\frac{1}{2} ft. high, W. of cor.} \] \[\text{Draw, drains Se.; asc. 100 ft. over a S. slope.} \] \[\text{Spur, slopes Se.; desc. 40 ft. over a Ne. slope.} \] \[\text{T39N} \] \[\text{Spur, slopes in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. \[\text{T39N} \] \[\	39.40	Draw, drains N. 80° E.; over broken land.
raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. 14.90 Draw, drains SE.; asc. 100 ft. over a S. slope. 61.00 Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. 79.00 Spur, slopes SE.; over broken land. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N S25 S36 R35E S31	40.00	
raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. 14.90 Draw, drains SE.; asc. 100 ft. over a S. slope. 61.00 Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. 79.00 Spur, slopes SE.; over broken land. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N S25 S36 R35E S31		⅓ s 36 .
raise a mound of stone, 2 ft. base, $l_{\Xi}^{\frac{1}{2}}$ ft. high, W. of cor. Draw, drains SE.; asc. 100 ft. over a S. slope. Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N S25 R36E R35E S31		
Spur, slopes SE.; desc. 40 ft. over a NE. slope. 77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. 79.00 Spur, slopes SE.; over broken land. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. 739N T39N S25 S36 R35E S31		raise a mound
77.70 Draw, drains S. 60° E.; asc. 140 ft. over a S. slope. 79.00 Spur, slopes SE.; over broken land. 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N T39N S25 R36E S36 R35E S31	14.90	Draw, drains SE.; asc. 100 ft. over a S. slope.
Spur, slopes SE.; over broken land. Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N T39N S25 R36E R35E S31	61.00	Spur, slopes SE.; desc. 40 ft. over a NE. slope.
Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N T39N S25 R36E R35E S31	77.70	Draw, drains S. 60° E.; asc. 140 ft. over a S. slope.
to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and 36, with brass cap mkd. T39N T39N S25 R36E S36 R35E S31	79.00	Spur, slopes SE.; over broken land.
S25 R36E S36 R35E S31	80.00	to bedrock, with a granite stone, mkd. with a cross (X), deposited at base, and in a mound of stone to top, for cor. of secs. 25 and
		S25 R36E S36
1971		1940