Independent Resurvey of Humboldt River Guide Meridian through T. 40 N.

1	Independent Resurvey of Humboldt River Guide Meridian through T. 40 N.
Chains	
	Land, rolling and broken. Soil, sandy clay, 3d rate.
	No timber; undergrowth, sagebrush and shadscale.
	Grazing, fair.
	North, bet. secs. 7 and 12.
(	Desc. 200 ft. over rolling land, along a W. slope, thru scattering undergrowth.
32.80	Draw, drains NE.; desc. 50 ft. over a N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a bottle containing cor. description deposited at base, for \frac{1}{4} sec. cor., with brass cap mkd.
	14
	s12 s7
	1940
	No suitable accessory.
47.50	Road, bears N. 55° E. and W.
58.90	Draw, drains E.; desc. 10 ft. over a N. slope.
64.60	Draw, drains S. 80° E.; asc. 130 ft. over a S. slope.
78.60	Top of ascent, bears E. and W. along an E. slope, desc. 10 ft.
80.0Ô	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.
	T 40 N R35E R36E S 1   S 6 S12   S 7
	1940
	of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, W. of cor.
	Land, rolling. Soil, sandy, rocky clay, 3d rate.
	No timber; undergrowth, sagebrush and shadscale.  Grazing, fair.
	North, bet. secs. 1 and 6.
	Desc. 90 ft. over rolling land, along an E. slope, thru dense undergrowth.
19.00	Leave E. slope; asc. 70 ft. over a S. slope.
30.30	Spur, slopes N. 70° E.; desc. 180 ft. over a N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<u>1</u>
	sı s 6
	1940