

Dependent Resurvey of the 8th Stan. Par. N. through R. 36 E.

Chains
 40.38 Over nearly level land, thru scattering undergrowth.
 The original standard $\frac{1}{4}$ sec. cor.; a pine post, 2 ins. sq., 28 ins. above ground, with illegible scribe marks.
 At cor. point
 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. post deposited at base, for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

S C
 $\frac{1}{4}$ S 34
 1940

No suitable accessory.

Thence

N. 88° 31' W., along S. bdy. sec. 34.

Over nearly level land, thru scattering undergrowth.

39.25 The standard cor. of secs. 33 and 34; an iron post, 2 ins. diam., 12 ins. above ground, mkd. and witnessed, as described in the official record.
 Land, nearly level.
 Soil, sandy, alkaline clay, 3d rate.
 No timber; undergrowth, sagebrush and greasewood.
 Grazing, poor.

 DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 38 N., R. 35 E.

"Reestablishment of the survey executed by H. B. Maxson, Deputy Surveyor, in 1888."

From the cor. of Tps. 38 and 39 N., Rs. 35 and 36 E., hereinbefore described, additional $\frac{1}{4}$ sec. and sec. cors. established at regular intervals of 40 and 80 chs., in departure for T. 39 N., R. 35 E.

N. 88° 51' W., along the N. bdy. of sec. 1.

Asc. 190 ft. over rolling mountainous land, thru scattering undergrowth.

11.10 Ridge, bears S. 60° E. and N. 60° W.; asc. 30 ft. on S. slope.

25.10 Leave ridge, bears N. 20° E. and S. 20° W.; desc. 80 ft. over a broken W. slope.

32.00 Draw, drains N. 50° W.; continue to desc. 210 ft. over a W. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap mkd.

$\frac{1}{4}$ S 36

1940

raise a mound
 of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

41.09 Proportional distance

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for $\frac{1}{4}$ sec. cor. of sec. 1, with brass cap mkd.