

DEPENDENT RESURVEY OF PORTION OF SUBDIVISIONAL LINES, T. 5 S., R. 37 E.

Chains

N. 0° 02' W., bet. secs. 7 and 8.

Descend 15 ft. over gentle NE. slope in Fish Lake Valley.

24.00

Wash, 20 lks. wide, 3 ft. deep, course N. 80° E.

39.78

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, monumented with a length of mine rail track, 18 ins. above ground, firmly set, in a low mound of earth. Alongside is the remains of the original cottonwood stake, with no legible marks.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, with brass cap marked



Deposit the remains of the original stake and length of mine rail track alongside the iron post, and raise a flat mound of stone, 4 ft. base, around post to top.

A windmill in sec. 8, bears N. 85° 53' E.

N. 0° 06' W., beginning new measurement.

Over gentle E. slope in Fish Lake Valley.

12.10

Wash, 10 lks. wide, 2 ft. deep, course winding E.

17.80

Abandoned old scraped highway, bears N. 35° W. and S. 40° E.

20.80

Oiled highway, bears S. 33 $\frac{1}{2}$ ° E. to Oasis and N. 33 $\frac{1}{2}$ ° W. to Nevada State Highway No. 3A.


39.76

The cor. of secs. 5, 6, 7, and 8, monumented with a length of mine rail track, 18 ins. above ground, firmly set in center of a low mound of earth and gravel. Find no remaining evidence of the original post.

This now becomes cor. No. 3 of Tract 40, also.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the length of mine rail track alongside the iron post and raise a mound of stone, 4 ft. base, around post to top.

The cor. is under a three strand barbwire fence, on steel posts, bears N. 88° 57' E. and S. 88° 57' W.

From this cor., the windmill in sec. 8, bears S. 50° 24' E.

Land, nearly level in Fish Lake Valley, drains northeasterly. Soil, alkaline clayloam, sand and gravel, 2nd rate. Undergrowth, light sagebrush and desert growth.