

DEPENDENT RESURVEY OF A PORTION OF THE N. BDY.
OF SEC. 1, T. 7 N., R. 42 E.

Chains
40.18

Intersect the original $\frac{1}{4}$ sec. cor., which is a decayed pine stake, 40 ins. long, 2 ins. sq., with marks nearly obliterated, lying at base of a small mound of earth; all traces of pits have disappeared.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the remains of the original stake deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 36

$\frac{1}{4}$ ———

S 1

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

From this cor., the triangulation station of the U.S. Coast and Geodetic Survey on Bald Mountain, bears N. $59^{\circ}54'$ E.

A monument on a cone-shaped peak bears N. $66^{\circ}06'$ E.
Highest point of Montgomery peak bears S. $54^{\circ}04'$ W.

Land, rolling.

Soil, sandy, shallow and gravelly and rocky; 4th rate.

Timber, none; undergrowth, short, stunted sagebrush, shadscale and a fair growth of grass.

DEPENDENT RESURVEY OF THE N. BDY. OF T. 6 N., R. 43 E.

Reestablishment of the survey executed by Glover and Perrin in 1881, and the establishment of corners for T. 7 N., R. 43 E.

The original SE. cor. of T. 7 N., R. 43 E., being missing, is reestablished by the method of double proportion; bet. the original cor. of secs. 1, 6, 7 and 12, T. 6 N., Rs. 43 and 44 E., and the original $\frac{1}{4}$ sec. cor. bet. secs. 31 and 36, T. 7 N., Rs. 43 and 44 E.; the original $\frac{1}{4}$ sec. cor. bet. secs. 6 and 31, Ts. 6 and 7 N., R. 44 E., and the original cor. of secs. 1, 2, 35 and 36, Ts. 6 and 7 N., R. 43 E. All of these original cors. for control were reestablished as hereinafter described.

The original cor. of secs. 1, 6, 7 and 12, T. 6 N., Rs. 43 and 44 E., is a granite stone $3 \times 10 \times 14$ ins., firmly set in a mound of stone, marked with 5 grooves on S. and 6 grooves on E. faces.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original stone deposited at the base, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T 6 N
R43E | R44E

S 1 | S 6

S12 | S 7

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

This cor. is situated 20 lks. E. of an unimproved road bearing nearly N. and S.

Thence

N. $0^{\circ}51'$ W., on true line bet. secs. 1 and 6, on blank line.

80.47

Proportionate distance. All traces of the original cor. of Ts. 6