## DEPENDENT RESURVEY OF THE W. BDY. OF T. 7 N., R. 44 E.

Chains	N. 0°40' E., on true line along W. bdy. of sec. 6,
	Over mountainous land, through dense timber and undergrowth; asc. 80 ft. over SE. slope.
8.00	Top of ridge, bears E. and W.; desc. 110 ft. over N. slope through scattering timber.
14.50	Slope changes, desc. 80 ft. over E. slope.
19.30	Slope changes; desc. 75 ft. along N. slope and along E. edge of gulch, course N. from S.
31.40	Ravine, course N.80°W.; asc. 75 ft. over S. slope.
38.00	Slope changes; asc. 10 ft. over W. slope.
38.79	Point 40 chs. in latitude from SE. cor. of sec. 1.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., for sec. 1 only, with brass cap mkd.
	½ S 1
_	1939
	of stone, 2 ft. base, $l_2^1$ ft. high, W. of cor.
740.00	Record distance; all trace of the original $\frac{1}{4}$ sec. cor. has disappeared.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \( \frac{1}{4} \) sec. cor. for sec. 6 only, with brass cap mkd.
	₹ s 6
	1939
	of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, E. of cor.
	Asc. 50 ft. over W. slope.
48.00	Slope changes; asc. 100 ft. over SW. slope.
56.50	Top of ridge, bears N.70°W. and S.60°E.; desc. 375 ft. over rocky N. slope.
70.70	Head of ravine, course N.20°W.; desc. 140 ft. along W. slope.
78.79	Point 80 chs. in latitude from SE. cor. of sec. 1.
	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock and in a mound of stone to top, for lot cor. 1-8 of sec. 1, T. 7 N., R. 43 E., with brass cap mkd.
	T 7N S 1—1 8 R43E 1939
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	Intersect the reestablished cor. of Ts. 7 and 8 N., R. 44 E., which is an iron post, 3 ins. diam., 10 ins. above ground, firmly set, with brass cap mkd.