

DEPENDENT RESURVEY OF THE W. BDY. OF T. 7 N., R. 44 E.

Chains

T 7N | T 8N  
      | R44E  
S 1 | S31  
     | S 6  
R43E | T 7N  
      | R44E

1939

from which,

- A piñon pine, 6 ins. diam., bears N.22°E., 3.52 chs. dist.,  
mkd. T8N R44E S31 BT.
- A piñon pine, 10 ins. diam., bears S.65½°E., 2.00 chs. dist.,  
mkd. T7N R44E S6 BT.

This cor. was established under Group No. 252.

Land, mountainous.  
Soil, sandy clay loam, medium texture, shallow, mixed with granite  
gravel and quartzite; many granite and quartzite outcroppings;  
4th rate.  
Timber, piñon pine, juniper and mahogany; undergrowth, sagebrush,  
buckbrush and a fair growth of grass.

DEPENDENT RESURVEY OF A PORTION OF THE S. BDY. OF T. 8 N., R. 43 E.

Dependent resurvey of a portion of the S. Bdy. of T. 8 N., R. 43 E.,  
reestablishing the survey executed by A. J. Hatch, D. H. Barker and  
E. L. Bridges, Deputy Surveyors, in 1873.

Beginning at the reestablished cor. of Ts. 7 and 8 N., Rs. 42 and 43  
E.,

S. 88°42' E., on true line bet. secs. 6 and 31,

Over rolling land, through dense short stunted undergrowth; asc.  
gradually along a W. slope, 80 ft. to wash.

- 1.80 Electric power transmission line, bears N.22°50'E. and S.22°50'W.
- 2.20 Telephone line combined with high power line, bears N. 22°50' E., and  
S. 22°50' W.
- 21.70 Wash, 20 lks. wide, 2 ft. deep, course N.75°W.; asc. 160 ft.
- 35.00 Top of spur, projects S. about 6.00 chs. dist.; desc. 30 ft.
- 38.00 Head of wash, course S.30°W.; asc. 20 ft.
- 39.01 Intersect the original ¼ sec. cor., which is a volcanic stone,  
5x10x13 ins., loosely set in a small mound of stone, with marks  
nearly obliterated.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to  
bedrock, with the original stone deposited at the base and in a  
mound of stone to top, for ¼ sec. cor. for sec. 31 only, with brass  
cap mkd.

¼ S 31

1939

Thence

- N. 84°57' E., on true line along S. bdy. of sec. 31.
- Asc. 35 ft.