

SURVEY OF S. BDY. OF T 8N., R. 43E.

Chains	
30.30	Wash, 30 lks. wide, course N.10°E.; desc. gradually.
38.43	Departure of 40.00 chs. East of the reestablished cor. of secs. 31 and 32, at which point Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite stone, 3x5x8, mkd. with a cross (X) deposited at the base, for $\frac{1}{4}$ sec. cor. for sec. 32 only, with brass cap mkd. $\frac{1}{4}$ S 32 <hr/> 1939 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
43.40	Wash, 10 lks. wide, course N.50°W.; asc. 25 ft.
52.60	Top of spur, slopes N.; desc. 100 ft.
65.60	Wash, course NW.; desc. 20 ft.
78.43	Intersect the reestablished cor. of secs. 31 and 32. Land, rolling mountainous. Soil, sandy, shallow, gravelly and rocky; 4th rate. Timber, very scattering juniper and pinon pine; undergrowth, sagebrush, buckbrush and a fair growth of grass.
SUBDIVISION OF T. 7 N., R. 43 E.	
	Beginning at the cor. of secs. 35 and 36 on the S. bdy. of the tp., North, on a true line on a sectional guide meridian bet. secs. 35 and 36, Over rolling mountainous land, through dense undergrowth; asc. gradually over SW. slope 10 ft.
2.40	Top of spur, slopes SE.; desc. 50 ft. over SE. slope.
8.00	Slope changes; desc. 100 ft. over SW. slope.
17.90	Gulch, 20 lks. wide, 1 ft. deep, course SW.; asc. 275 ft. over SW. slope.
39.70	Top of spur, slopes S.30°E.; desc. 95 ft. over SE. slope.
40.56	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\frac{1}{4}$ S35 S36 1939 raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. from which, NW. cor. of concrete water tank bears N.82°E. Desc. 60 ft.
45.40	Wash, 25 lks. wide, 1 ft. deep, course NE.; asc. 30 ft.
51.80	Point of spur, slopes W.; desc. 10 ft.
59.80	Hillside drain, course SE.; asc. 40 ft.