

SUBDIVISION OF T. 7 N., R. 43 E.

Chains	
24.60	Top of rocky spur, slopes SW.; desc. 210 ft. over a rocky NW. slope.
37.00	Gulch, course NW.; asc. 10 ft.
38.30	Point of rocky spur, projects W.; desc. 80 ft.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S\ 2 \quad \quad S\ 1 \\ 1940 \end{array}$ <p style="text-align: right;">from which,</p> <p>A piñon pine, 7 ins. diam., bears N. $59\frac{1}{2}^{\circ}$E., 90 lks. dist., mkd. $\frac{1}{4}$ S1 BT.</p> <p>A piñon pine, 5 ins. diam., bears S. 68°W., 116 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p>Desc. 10 ft.</p>
40.70	Ravine, course SW.; asc. 325 ft. over series of crags along a SE. slope.
52.50	Top of rimrock and crags, bears N. 70° E. and W.; thence asc. 60 ft.
63.40	Top of ridge, bears E. and W.; desc. 15 ft.
72.70	Head of wash, course W.; desc. 30 ft.
76.70	Top of ridge, bears NW. and SE.; desc. 95 ft. over NE. slope.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for cor. of lots 4-5 of sec. 1, and lots 1-8 of sec. 2, with brass cap mkd.
	$\begin{array}{c} 1\ 4 \\ S2 \quad \quad S1 \\ 8\ 5 \\ 1940 \end{array}$ <p style="text-align: right;">from which,</p> <p>A piñon pine, 10 ins. diam., bears N. $57\frac{1}{2}^{\circ}$W., 100 lks. dist., mkd. L 1 S2 BT.</p> <p>A piñon pine, 6 ins. diam., bears S. 77°E., 31 lks. dist., mkd. L 5 S1 BT.</p> <p>Desc. 80 ft. over NE. slope.</p>
86.36	Intersect the N. bdy. of the tp.
	At the point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 1 and 2, with brass cap mkd.
	$\begin{array}{c} T\ 8N\ R43E \\ S35 \\ \hline S\ 2 \quad \quad S\ 1 \\ T\ 7N\ R43E \\ CC \\ 1940 \end{array}$ <p style="text-align: right;">from which</p> <p>A piñon pine, 10 ins. diam., bears S. 48°E., 39 lks. dist., mkd. T7N R43E S1 CC BT.</p>