## SUBDIVISION OF T. 7 N.R. 43 E.

Chains 80.00

Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground to bedrock, with a sandstone, 3x5x6 ins., mkd. (X) deposited at the base and in a mound of stone to top, for cor. of lots 4-5 of sec. 4 and lots 1-8 of sec. 5, with brass cap mkd.

80.10 Unimproved road, bears N.85°E. and S.85°W.; desc. 25 ft.

86.11 Intersect the S. bdy. of T. 8 N., R. 43 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.

raise a mound

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

From this closing sec. cor., the cor. of secs. 32 and 33 on the S. bdy. of T. 8 N., R. 43 E., bears East, 4.14 chs. dist.

Land, rolling mountainous.

Soil, sandy, gravelly and rocky; 4th rate.

Timber, piñon pine and juniper; undergrowth, sagebrush and a fair growth of grass.

At midpoint on the N. bdy. of sec. 4,

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock with a sandstone 4x6x8 ins., mkd. with a cross X deposited at the base, and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor. for sec. 4 only, with brass cap mkd.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. for sec. 33 on the S. bdy. of T. 8 N., R.  $\frac{1}{4}$ 3 E., bears East,  $\frac{1}{4}$ .10 chs. dist.

From the cor. of secs. 31 and 32 on the S. bdy. of the tp.,

N. 0°03' W., bet. secs. 31 and 32,

Over rolling mountainous land, through dense low undergrowth; asc. 15 ft. over broken SW. slope.

6.50 Top of low spur, projects W.; desc. 10 ft.

8.50 Small wash, course W.; asc. 30 ft.

20.00 Top of spur, slopes W.; desc. 5 ft.

26.00 | Wash, course W.; asc. 25 ft.

38.79 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground,