

SUBDIVISION OF T. 7 N., R. 43 E.

Chains

West, on a true line bet. secs. 7 and 18,

Over rolling mountainous land, through scattering timber and dense undergrowth; asc. 10 ft. along a broken N. slope.

- 8.00 Point of spur, slopes NW.; desc. 35 ft. Leave timber, bears NE. and SW.
- 12.70 Wash, course NW.; asc. 25 ft.
- 17.60 Point of spur, slopes NW.; desc. 120 ft.
- 32.00 Wash, course NW.; asc. 60 ft.
- 39.20 Top of spur, slopes N. for 2.00 chs., thence NW.; desc. 10 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S. 7
 $\frac{1}{4}$ ———
 S 18
 1940

Desc. 135 ft. over broken N. slope.

- 57.50 Unimproved road, bears N.30°E. and S.30°W.; desc. 25 ft.
- 66.70 Unimproved road, bears N.50°W. and S.50°E.; desc. 20 ft.
- 72.38 Intersect the Reese River Guide Meridian.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 7 and 18, with brass cap mkd.

T 7N | T 7N
 R42E | S 7
 | ——— CC
 | S18
 S13 | R43E
 1940

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this closing cor., the cor. of secs. 12 and 13 on the E. bdy. of T. 7 N., R. 42 E., bears N. 0°09' E., 2.82 chs. dist.

Land, rolling mountainous.
 Soil, sandy, gravelly and rocky; 4th rate.
 Timber, scattering piñon pine and juniper; undergrowth, sagebrush, shadscale, greasewood and a fair growth of grass.

At midpoint on the W. bdy. of sec. 18,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 18 only, with brass cap mkd.

| $\frac{1}{4}$ S 18
 1940

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this $\frac{1}{4}$ sec. cor., the $\frac{1}{4}$ sec. cor. for sec. 13 on the E. bdy. of T. 7 N., R. 42 E., bears N. 0°57' E., 2.69 chs. dist.