SUBDIVISION OF T. 7 N.R. 43 E.

Chains Desc. 15 ft. over SW. slope. Dry wash, course N.60°W.; asc. 5 ft. 43.90 48.45 Top of low spur, slopes N.60°W.; desc. 35 ft. From this point, center of maintenance station house, bears S.28°35'W. Wash, 1.00 ch. wide, 3 ft. deep, course N.60°W.; desc. 110 ft. over 53.27 broken W. slope. 71.65 Intersect the Reese River Guide Meridian. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd. R42E S 6 S12 R43E

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this closing sec. cor., the cor. of secs. 1 and 12 on the E. bdy. of T. 7 N., R. 42 E., bears N. 0°19' E., 3.32 chs. dist.

1940

Land, rolling mountainous.
Soil, sandy, gravelly and rocky; 4th rate.
Timber, none; undergrowth, sagebrush, shadscale, greasewood and a fair growth of grass.

At midpoint on the W. bdy. of sec. 7,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 7 only, with brass cap mkd.

1 s 7

1940

raise a mound

3.505

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this $\frac{1}{4}$ sec. cor., the $\frac{1}{4}$ sec. cor. for sec. 12 on the E. bdy. of T. 7 N.,R. 42 E., bears N. 0°32' E., $3.50\frac{1}{8}$ chs. dist.

At a point on the W. bdy. of sec. 6, 40 chs. in latitude from the closing cor. of secs. 6 and 7,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., for sec. 6 only, with brass cap mkd.

1940

raise a mound

of stone, 2 ft. base, 1 ft. high, E. of cor.

From this $\frac{1}{4}$ sec. cor., the $\frac{1}{4}$ sec. cor. on E. bdy. of sec. 1, T. 7 N., R. 42 E., bears N. 0°28' E., 3.39 chs. dist.

At a point on the W. bdy. of sec. 6, 80 chs. in latitude from the closing cor. of secs. 6 and 7,

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to

U. S. GOVERNMENT PRINTING OFFICE 6—8155