

## Survey of the West Boundary of T.8 N., R.44 E., M.D.M.

## Chains

7.20 Wash, course S.20°E., from N.80°W.; asc. 55 ft.

9.33 Point for the cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bedrock, and in a mound of stone to top, with brass cap mkd.

T8N		T8N
S 1		R44E
S 12		S 6
R43E		

1939

from which

A pinon pine, 6 ins. diam., bears S.50°W.,  
39 lks. dist., mkd. T8N R43E S12 BT

A pinon pine, 10 ins. diam., bears N.60°W.,  
21 lks. dist., mkd. T8N R43E S1 BT

13.80 Top of divide, bears S.70°W., and N.20°E.; asc. 60 ft. along W. side of ridge.

21.80 Change of slope to NW.; desc. 20 ft.

22.60 Ravine, course S.30°W., from N.20°E.; asc. 170 ft.

28.80 Spur, slopes S.20°E.; asc. 180 ft. over broken E. slope.

38.30 Top of rocky knoll on ridge, bears S.10°W., and NE.  
Desc. 25 ft.

40.00 Point for  $\frac{1}{4}$  sec. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with brass cap mkd.

$\frac{1}{4}$ S6
------------------

1939

from which

A pinon pine, 24 ins. diam., bears N.30 $\frac{1}{2}$ °E.,  
54 lks. dist., mkd.  $\frac{1}{4}$  S6 BT

A pinon pine, 6 ins. diam., bears S.32 $\frac{1}{2}$ °E.,  
91 lks. dist., mkd.  $\frac{1}{4}$  S6 BT

Bury a quartz rock, 6x6x4 ins., mkd. with a cross, X,  
alongside, and raise a mound of stone around post to top.

Asc. 35 ft. along W. slope.

45.00 Top of spur, slopes SE., from low peak 5 chs. to west.  
Continue ascent 50 ft. over SE. slope.

48.00 Head of wash, course S.10°E.; asc. 70 ft.

49.33 Point for  $\frac{1}{4}$  sec. cor. of sec. 1.