

Dependent Resurvey of a Portion of the Subdivision of  
T. 8 N., R. 43 E.

Chains

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. raise a mound

Land, rolling mountainous.  
Soil, sandy, gravelly and rocky; 4th rate.  
Timber, none; undergrowth, sagebrush, shadscale and a fair growth of grass.

From the cor. of secs. 29, 30, 31 and 32.

N.  $0^{\circ} 24'$  E., on true line bet. secs. 29 and 30. (S.  $\frac{1}{2}$  mile)

Over rolling mountainous land, through dense short undergrowth, asc. 5 ft.

5.50 Top of spur, slopes NW.; desc. 15 ft.

11.50 Dry wash, 30 lks. wide, 3 ft. deep, course NW.; desc. 20 ft.

22.30 Dim road, bears NE. and SW.

23.90 Telephone line, from Manhattan to Tonopah, Nevada, bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W.

24.70 Power line, bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W.; desc. 10 ft.


30.10 Dry wash, 20 lks. wide, 2 ft. deep, course N.  $30^{\circ}$  W.; desc. 25 ft.

37.50 Dry wash, 20 lks. wide, 1 ft. deep, course NW.; desc. 10 ft.

40.24 The original  $\frac{1}{4}$  sec. cor., which is a granite stone,  $3\frac{1}{2} \times 1\frac{1}{2} \times 1\frac{1}{2}$  ins., above ground, firmly set, mkd.  $\frac{1}{4}$  on W. face.

At point for corner

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original stone deposited at the base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a mound

Thence

N.  $0^{\circ} 28'$  E., on true line bet. secs. 29 and 30. (N.  $\frac{1}{2}$  mile)

Desc. gradually 75 ft. over a general NW. slope to sec. cor.

16.00 Dry wash, 20 lks. wide, 1 ft. deep, course NW.

22.50 Old dim unused road, bears NE. and SW.

39.00 Wash, 30 lks. wide, 1 ft. deep, course NW.

40.09 The original cor. of secs. 19, 20, 29 and 30, which is a granite stone,  $10 \times 1\frac{1}{2} \times 1\frac{1}{2}$  ins., above ground, firmly set, mkd. and witnessed as described in the official record.