

Chains

Land, mountainous.
Soil, sandy, shallow, gravelly and rocky; 4th rate.
Timber, scattering pinion pine and juniper; undergrowth,
sagebrush, shadscale and a fair growth of grass.

N. 0° 01' W., on the W. bdy. of sec. 1.

Over mountainous land, through scattering timber and
dense undergrowth, asc. 50 ft. over S. slope.

10.00 Top of spur, slopes S. 75° W.; desc. 10 ft.

12.00 Wash, course W.; asc. 20 ft.

21.60 Top of spur, slopes S. 80° W.; desc. 20 ft.

27.80 Wash, course S. 80° W.; asc. 150 ft. over SE. slope.

36.03 Proportionate distance, along E. bdy. sec. 2.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of sec. 2 only, with brass
cap mkd.

$\frac{1}{4}$ S2

1940

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

37.50 Top of spur ridge, bears W. 2.00 chs. to peak, and E.
5.00 chs. to saddle; desc. 35 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
the ground to bedrock, with a granite stone, 4x6x8 ins.,
mkd. X, deposited at the base, and in a mound of stone
to top, for $\frac{1}{4}$ sec. cor., for sec. 1 only, with brass
cap mkd.

$\frac{1}{4}$ S1

1940

Desc. 105 ft. over broken N. slope.

46.60 Wash, 10 lks. wide, course NW. for 3.00 chs. then W.;
asc. 10 ft. along a broken SW. slope.

51.50 Top of low spur, slopes S. 80° W.; desc. 10 ft.

56.40 Wash, course S. 60° W.; asc. 20 ft.

59.20 Top of low spur, slopes SW.; desc. 5 ft.

63.20 Wash, course SW.; asc. 30 ft.

69.00 Top of spur, slopes SW.; desc. 25 ft.

76.23 Intersect the S. bdy. of T. 9 N., R. 43 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for closing cor. of secs. 1 and 2, with
brass cap mkd.