

## Dependent Resurvey of a portion of the E. Bdy. of T. 9 N., R. 45 E.

Chains	
	N. 2° 33' E., bet. secs. 1 and 6. Over mountainous land, through scattering timber and dense undergrowth, desc. 45 ft. along a broken NE. slope.
4.40	Unimproved road, bears N. 80° W. and S. 80° E.
5.50	Meadow Creek, 6 lks. wide, 3 ins. deep, flowing stream, course E.; asc. 55 ft. over S. slope.
13.30	Point of spur slopes E.; asc. 65 ft. over NE. slope.
21.70	Wash, course E.; asc. 140 ft. over SE. slope.
25.30	Top of spur, slopes E.; desc. 25 ft.
32.70	Top of spur, projects E.; desc. 10 ft.
38.33	Proportionate point, Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, with a granite stone, 4x6x8 ins., mkd. with a cross (x), deposited at the base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 1   S 6 1939
	from which
	A pinon pine, 5 ins. diam., bears S. 45 $\frac{1}{2}$ ° E., 55 lks. dist., mkd. $\frac{1}{4}$ S 6 BT.
	A pinon pine, 5 ins. diam., bears S. 32 $\frac{1}{4}$ ° W., 40 lks. dist., mkd. $\frac{1}{4}$ S 1 BT.
	Asc. 130 ft. over NE. slope.
39.80	Hillside drain, course SE.; asc. 80 ft. over a S. slope.
45.20	Top of spur, bears E. and slopes W. to a saddle 3.00 chs. dist.; desc. 125 ft. over N. slope.
62.50	Dry wash, course E.; asc. 80 ft. over S. slope.
76.66	The original cor. of Tps. 9 and 10 N., Rs. 45 and 46 E., a granite stone, 9x10x16 ins., firmly set in ground, mkd. as described in the original record. At point for cor., with the original corner stone deposited at the base, Set an iron post, 3 ft. long, 3 ins. diam., 3 ins. in the ground to bedrock, and supported in a large mound of stone to top, for cor. of Tps. 9 and 10 N., Rs. 45 and 46 E., with brass cap mkd.

T 10 N  
 R45E R46E  
 S36 | S31  
 S 1 | S 6  
 T 9 N  
 1939

from which