

## Survey of the South Boundary of T. 10 N., R. 45 E.

Chains 16.70	Hillside drain, course S. 50° E.; asc. 85 ft. along E. slope.
21.80	Top of spur, slopes S. 50° E.; asc. 40 ft. along broken S. slope.
36.80	Hillside drain, course SE.; asc. 65 ft. along E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 32 only, with brass cap mkd.
	$\frac{1}{4}$ S 32
	-----
	1939
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Asc. 20 ft. along SE. slope.
43.80	Top of spur ridge, bears N. 70° E. and S. 70° W.; asc. 30 ft. along N. slope.
56.60	Top of spur, projects N.; desc. 150 ft. along N. slope.
79.50	Dim road, bears N. 50° E. and S. 50° W.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 31 and 32, with brass cap mkd.
	T10N   R45E S31   S32
	-----
	S 5 T 9 N 1939
	raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Land, mountainous. Soil, sandy, gravelly and rocky; 4th rate. Timber, scattering pinon pine, juniper and mahogany. Undergrowth, sagebrush. Grazing, good.
	West, along the S. bdy. of sec. 31.
	Over mountainous land, through scattering timber and dense undergrowth, desc. 15 ft.
1.40	Hillside drain, course N. 60° E.; asc. 160 ft. over E. slope.
7.20	Dim road, bears N. and S.; asc. 340 ft. over E. slope.
26.40	Top of spur, slopes S. 20° E.; desc. 70 ft. along a S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 31 only, with brass cap mkd.
	$\frac{1}{4}$ S 31
	-----
	1939