

Survey completing the Subdivisions of T. 9 N., R. 45 E.

Chains	
	T10N R45E S35 <hr style="width: 10%; margin: auto;"/> 2 1 S 2 T 9 N 1939
	from which
	A pinon pine, 6 ins. diam., bears N. 53° E., 4 lks. dist., mkd. T 10 N R 45 E S 35 BT.
	A pinon pine, 6 ins. diam., bears S. 12° W., 17 lks. dist., mkd. T 9 N R 45 E S 2 L C BT.
89.15	The cor. of secs. 35 and 36, T. 10 N., R. 45 E.
92.24	The true point for cor. of secs. 1 and 2 only, hereinbefore described.
<p>From the cor. of secs. 33 and 34, on the S. bdy. of the tp. which is monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the survey of T. 8 N., R. 45 E.</p> <p>N. 0° 01' W., bet. secs. 33 and 34.</p> <p>Over rolling mountainous land, through scattering timber and dense undergrowth, desc. 10 ft.</p>	
5.90	Wash, 10 lks. wide, 2 ft. deep, course SW.; asc. gradually, 90 ft. over a general S. slope to $\frac{1}{4}$ sec. cor.
19.60	Wash, 10 lks. wide, 2 ft. deep, course S. 30° W.
23.50	Unimproved road, bears N. 80° W. and S. 80° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with a quart of charcoal deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S33 S34 1939
47.50	Top of low spur, 15 ft. above $\frac{1}{4}$ sec. cor., slopes S. 50° E.; desc. 5 ft.
50.90	Dry wash, 10 lks. wide, 2 ft. deep, course S. 50° E.; asc. 90 ft. over a gradual S. slope to sec. cor.
61.20	Wash, 10 lks. wide, 2 ft. deep, course S. 60 E.
64.60	Wash, 5 lks. wide, 1 ft. deep, course S. 30° E.
69.60	Old dim road, bears N. 70° W. and S. 70° E.
75.90	Wash, 10 lks. wide, 2 ft. deep, course S. 52° E.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap mkd.