

## Survey completing the Subdivisions of T. 9 N., R. 45 E.

Chains	
	No other suitable trees available.
	Asc. 25 ft. over NE. slope.
41.90	Top of ridge, bears N. 60° W. and S. 60° E.; whence another spur, projects S. 30° E.; desc. 175 ft. over a broken SW. slope.
62.00	Head of ravine, course S. 25° E.; asc. 160 ft. over E. slope.
73.20	Top of spur, slopes S. 20° E.; asc. 30 ft. over a SW. slope.
80.00	The cor. of secs. 3, 4, 9, and 10.
	Land, mountainous. Soil, sandy, gravelly and rocky; 4th rate. Timber, mahogany, pinon pine and juniper; undergrowth, sagebrush. Grazing, good.
	N. 0° 01' W., bet. secs. 3 and 4.
	Over mountainous land, through scattering timber and dense undergrowth, asc. 110 ft. over SW. slope.
6.50	Top of ridge, bears E. and W.; desc. along broken W. slope, 90 ft.
14.30	Head of hillside drain, course W.; asc. 5 ft.
18.75	Top of spur, slopes N. 60° W.; desc. 400 ft. over N. slope.
34.00	Ryecraft Canyon, with a small stream, 3 lks. wide, 2 ins. deep, course N. 75° E.; asc. 80 ft. over S. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\   \\ S\ 4\   \ S\ 3 \\   \\ 1940 \end{array}$
	from which
	A mahogany, 6 ins. diam., bears S. 86° E., 281 lks. dist., mkd. $\frac{1}{4}$ S 3 BT.
	The W. end of a trough at Sagehen Spring, bears N. 82½° E., 11.52 chs. dist.; from which a round metal tank, bears SE. 20 lks. from trough.
	Asc. 90 ft. over SE. slope:
47.60	Top of spur, slopes E.; desc. 90 ft. over N. slope.
52.50	Wash, course E.; desc. 70 ft.
64.50	Wash, course S. 70° E.; asc. 130 ft. over S. slope.
71.40	Top of ridge, bears E. and W.; desc. 90 ft. over N. slope.
75.45	Intersect the N. bdy. of the Tp.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the