

274

Township 13 North, Range 58 East

Chains

The tests of the arcs were repeated by daily noon observations, and the meridional indications of each instrument was verified frequently throughout the survey. The instruments were at all times kept in satisfactory adjustments.

Dependent Resurvey, Portion of the South Boundary, T. 13 N., R. 58 E.

Partial Reestablishment of the Survey Executed by
E. B. Monroe, Deputy Surveyor, in 1874.

Beginning at the original cor. of Ts. 12 and 13 N., Rs. 58 and 59 E., which is monumented with a trachyte stone, 12x10x6 ins., firmly set in ground, and marked with 6 grooves on N., S., E. and W. faces.

West, on the S. bdy. of sec. 36.

Note: This line was surveyed originally as a common boundary for sections to N. and S., but in the present work, corners are remonumented for sections of T. 13 N., R. 58 E. only.

Over mountainous land, through dense undergrowth and scattering timber; desc. 30 ft. over short NW. slope.

- 2.50 Trail, bears NE. and SW.
- 6.70 Wash, 20-lks. wide, 3-ft. deep, course NE.
- 8.50 Unimproved road, bears NE. and SW.; asc. 40 ft. over SE. slope.
- 16.00 Long spur ridge, bears NE. and SW., crest slopes gradually to NE.; desc. 40 ft. over NW. slope.
- 24.00 Wash, with trickle of water in bed 30 lks. wide, 3 ft. deep, course NE.; asc. 30 ft. over gradual SE. slope.
- 39.57 Point for the S. $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Corner not remonumented.
- Asc. 30 ft. over SE. slope.
- 47.00 Spur ridge, bears NE. and SW.; crest slopes gradually to NE.; desc. 25 ft. over NW. slope.
- 56.00 Head of wash, drains N. 60° E.; asc. 50 ft. over NE. and E. slopes.
- 65.00 Same ridge, bears NW. and SE.; crest slopes gradually to SE.; desc. 50 ft. over SW. slope.
- 79.14 The original cor. of secs. 1, 2, 35 and 36, which is monumented with a limestone, 8x9x25 ins., firmly set in ground, and marked with 1 groove on E. and 5 grooves on W. faces. This corner now to function for cor. of secs. 35 and 36 only.
- At the corner point
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13N R58E

S35|S36

1941