

Survey of the West Boundary of T. 13 N., R. 58 E.

Chains

40.00

Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S 1 | S 6 \\ 1941 \end{array}$$
Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, around the iron post.

from which

A pinon, 14 ins. diam., bears N. 80° E., 118 lks. dist., mkd. $\frac{1}{4}$ S6 BT.A pinon, 6 ins. diam., bears S. $88\frac{1}{2}^{\circ}$ W., 81 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Asc. 45 ft. over SE. slope.

46.00

Hillside drain, course S. 75° E.; asc. 50 ft. over SE. slope.

48.60

Top of spur ridge, bears S. 75° E. 10.00 chs. to a saddle, and W.; desc. 65 ft.

52.90

Head of gulch, course N. 80° E.; asc. 170 ft. along broken rocky SE. slope.

62.00

Top of spur, slopes E.; asc. 100 ft. along rocky E. slope near crest of spur.

75.60

The cor. of Ts. 13 and 14 N., Rs. 57 and 58 E., hereinbefore described.

Land, mountainous.

Soil, sandy clay loam, shallow, gravelly and rocky.

Timber, pinon, juniper and mahogany; undergrowth, sagebrush, buckbrush, brierbrush and a good growth of grass.

Dependent Resurvey of a Portion of the Subdivision of
T. 13 N., R. 58 E.

Reestablishment of the Survey Executed by
E. B. Monroe, Deputy Surveyor, in 1874.

Beginning at the original cor. of secs. 2, 3, 10 and 11, which is monumented with a limestone, 8x10x12 ins., firmly set in a mound of stone, mkd. with 5 notches on S. and 2 notches on E. edges.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T13N R58E \\ S3 | S2 \\ \hline S10 | S11 \\ 1941 \end{array}$$

Deposit the old corner stone at base of the iron post.