

## Survey of a Portion of the Subdivision of T. 13 N., R. 58 E.

## Chains

Beginning at the cor. of secs. 33 and 34, on the S. bdy. of the township, hereinbefore described.

North, on a Sectional Guide Meridian, bet. secs. 33 and 34.

Over high rugged mountainous land, through dense timber and scattering undergrowth; asc. 125 ft. over ledges and crags over a SW. slope.

5.10 Spur, projects W.; desc. 200 ft. over series of ledges and very rocky NW. slope.

X 11.00 Steep hillside gulch, course S. 60° W.; desc. 225 ft. over NW. slope.

19.30 Deep ravine, course S. 70° W. from SE.; asc. 190 ft. over S. slope.

24.60 Base of nearly vertical cliff, 100 ft. high, bears E. and W.

25.60 Top of cliff; thence asc. 5 ft. along gradual W. slope.

25.75 Top of spur, projects W.; desc. 325 ft. over ledges and crags, facing generally to N. and NW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 33 and 34.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 33 | S 34  
1941

from which

A foxtail pine, 9 ins. diam., bears S. 22 $\frac{1}{2}$ ° E., 44 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.

A balsam fir, 9 ins. diam., bears N. 79 $\frac{1}{2}$ ° W., 43 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

Desc. 110 ft. over a steep N. slope.

43.20 Steep hillside drain, course NW.; desc. 210 ft. over NW. slope.

54.70 Ravine, course S. 80° W., at junction of ravines from S. 60° E. and N. 80° E.; asc. 930 ft. over a steep rugged S. slope, over a series of ledges and crags.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13N R58E  
S28 | S27  
S33 | S34  
1941

from which

A mahogany, 9 ins. diam., bears N. 51° E., 42 lks. dist., mkd. T13N R58E S27 BT.

A mahogany, 10 ins. diam., bears S. 51° E., 51 lks. dist., mkd. T13N R58E S34 BT.