

405

Survey of the Subdivision, T. 13 N., R. 57 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 19
S 30
1941

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Desc. 20 ft. over gradual SW. slope.

52.30 Enter nearly level valley land, bears N. and S.; thence through dense white sagebrush.

79.20 Wash, 6 lks. wide, 3 ft. deep, course S. 5° W.

80.00 Point for the cor. of lots 10 and 11 of sec. 19, and of lots 2 and 3 of sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S 19
 $\frac{10}{3} \mid \frac{11}{2}$
S 30
1941

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

83.60 Dry channel of Bull Creek, 25 lks. wide, with cut banks 4 ft. high, course S. 10° E.; asc. 5 ft. along gradual S. slope to closing cor.

87.00 Unimproved road, bears N. 25° W. and S. 20° E.

90.28 Intersect the E. bdy. of sec. 25, T. 13 N., R. 56 E., at point for closing cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T13N T13N
S25 S19
R56E S30 CC
R57E
1941

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this cor., the reestablished cor. of secs. 24 and 25, on the E. bdy. of T. 13 N., R. 56 E., hereinbefore described, bears N. $0^{\circ} 15'$ E., 10.78 chs. dist.

Land, part rolling to broken, and part nearly level valley. Soil, light sandy clay loam, medium texture, gravelly and rocky in the E. 52.00 chs.; remainder, sandy adobe free from rocks, alkaline.

Timber, none; undergrowth, black, white and yellow sagebrush, shadscale, greasewood, and a fair growth of grass.

At the point for the W. $\frac{1}{4}$ sec. cor. of sec. 30, and at midpoint on the W. bdy. of sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.