

Survey of the Subdivision, T. 13 N., R. 57 E.

Chains	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
48.00	Low flat spur, slopes S. 15° W.; desc. 35 ft. over gradual SW. slope.
69.30	Wash, course S. 38° W.; asc. 15 ft. over SE. slope.
72.00	Top of low spur, slopes S. 20° W.; desc. 10 ft. over SW. slope.
73.70	Wash, 30 lks. wide, 8 ft. deep, course S. 30° W.; desc. 5 ft. along gradual S. slope.
75.50	Enter nearly level valley land, bears N. 10° E. and S. 10° W.
80.00	Point for the cor. of lots 10 and 11, sec. 18, and of lots 2 and 3, sec. 19. <div>S 18 10 11 3 2 S 19 1941</div>
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
85.90	Unimproved road, bears N. 10° W. and S. 10° E. Freeland
88.90	Channel of/Wash, 10 lks. wide, 3 ft. deep, course S. 10° W.
89.86	Intersect the E. bdy. of sec. 24, T. 13 N., R. 56 E., at point for closing cor. of secs. 18 and 19. <div>T13N T13N S24 S18 R56E S19 CC R57E 1941</div>
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. From this corner, the reestablished cor. of secs. 13 and 24, on the E. bdy. of T. 13 N., R. 56 E., hereinbefore described, bears N. 0° $15'$ E., 11.12 chs. dist. Land, rolling to nearly level desert valley. Soil, light sandy clay loam, medium texture, gravelly and rocky in the E. 75.00 chs.; soil in the level valley land is sandy adobe, alkaline, and free from rocks. Timber, none; undergrowth, sagebrush, greasewood, rabbit brush, and a fair growth of grass.
	At the point for the W. $\frac{1}{4}$ sec. cor. of sec. 19, at midpoint on the W. bdy. of sec. 19. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd. <div> $\frac{1}{4}$ S19 1941</div>