

411

Survey of the Subdivision, T. 13 N., R. 57 E.

Chains	
35.40	Wash, course S. 25° W.; desc. slightly along gradual S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd. <div>S 7 $\frac{1}{4}$ S 18 1941</div> Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
50.80	Wash, 10 lks. wide, 2 ft. deep, course S. 5° W.; desc. 25 ft. along gradual SW. slope.
72.00	Top edge of bench, bears NE. and SW.; desc. 20 ft. over SW. slope to wash.
80.00	Point for the cor. of lots 10 and 11, sec. 7, and of lots 2 and 3, sec. 18. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd. <div>S 7 10 11 3 2 S 18 1941</div> Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
81.90	Wash, 20 lks. wide, 4 ft. deep, course S. 30° W.; asc. 10 ft. along gradual S. slope.
83.10	Flat spur, slopes S. 30° W.; unimproved road, bears N. 30° E. and S. 30° W. Desc. 15 ft. over short SW. slope.
84.60	Channel of Freeland Canyon Wash, 10 lks. wide, 3 ft. deep, course S. 35° W.; thence over nearly level desert valley land.
89.30	Unimproved road, bears N. and S.
89.50	Intersect the E. bdy. of sec. 13, T. 13 N., R. 56 E., at point for closing cor. of secs. 7 and 18. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd. <div>T13N T13N S13 S7 CC R56E S18 R57E R57E 1941</div> Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor. From this cor., the reestablished cor. of secs. 12 and 13, on the E. bdy. of T. 13 N., R. 56 E., hereinbefore described, bears N. 0° 15' E., 11.34 chs. dist. Land, rolling desert valley. Soil, light sandy clay loam, medium texture, gravelly and rocky. Timber, none; undergrowth, sagebrush, shadscale, greasewood, rabbit brush, jointbrush, and a fair growth of grass.