Chains

Desc. 30 ft. over bench land sloping gradually to SW.

80.00

Point for the cor. of lots 14 and 15, sec. 6, and of lots 2 and 3, sec. 7.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

S 6

14 | 15

3 | 2

5 7

1941

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Desc. 15 ft. over gradual SW. slope.

84.90

Wash, 20 lks. wide, 2 ft. deep, course S. 50° W.

Intersect the E. bdy. of sec. 12, T. 13 N., R. 56 E., at point for closing cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

From this cor., the reestablished cor. of secs. 1 and 12, on the E. bdy. of T. 13 N., R. 56 E., hereinbefore described, bears N. 0° 15' E., 11.58 chs. dist.

Land, rolling desert valley.
Soil, light sandy clay loam, medium texture, gravelly and rocky.
Timber, none; undergrowth, sagebrush, shadscale, greasewood, rabbit brush, jointbrush, and a fair growth of grass.

At the point for the W. 4 sec. cor. of sec. 7 and at midpoint on the W. bdy. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground to bedrock, with brass cap mkd.

Raise a supporting mound of stone, 3 ft. base, 20 ins. high, around the iron post.

From this cor., the E.  $\frac{1}{4}$  sec. cor. of sec. 12, T. 13 N., R. 56 E., hereinbefore described, bears N. 0° 15' E., 11.46 chs. dist.

At the point for the W. 4 sec. cor. of sec. 6, and 40.00 chs. in northing from the closing cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.