

536

Dependent Resurvey W. Bdy. T. 45 N., R. 64 E.

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for closing cor. of T. 45 N., Rs. 63 and 64 E., with brass cap mkd.

T46N	R63E
S36	
S 1	S 6
R63E	R64E
T45N	
CC	
1940	

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

From point of intersection, the standard $\frac{1}{4}$ cor. of sec. 36, T. 46 N., R. 63 E., bears West, 14.66 chs. dist.

From point of intersection, the original closing cor. of T. 45 N., Rs. 63 and 64 E., bears N. $0^{\circ} 03'$ E., 3 lks. dist.; a basalt stone, 18x7x5 ins., mkd. with 6 notches on the E., W., and S. edges, firmly set in the ground, and in a mound of stone. Reset the original closing township cor. 18 ins. in the ground with the top of the stone flush with the surface of the ground.

Land, rolling mountainous.

Soil, gravelly, 2nd rate.

Timber, none.

Undergrowth, sagebrush.

Grazing, good.

DEPENDENT RESURVEY OF THE SUBDIVISION OF T. 45 N., R. 64 E.

Reestablishment of the Survey Executed by Deputy Surveyors
Monroe and McClellan in 1881.

Begin the dependent resurvey at the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.

N. $0^{\circ} 13'$ E., bet. secs. 35 and 36.

Desc. 70 ft. over W. slope.

6.00 Wash, course W.; asc. 70 ft. along broken W. slope.

15.00 Desc. 150 ft. over broken NW. slope.

21.30 Minor wash, course N. 80° W.; asc. 50 ft. along broken W. slope.

26.00 Desc. 150 ft. over broken NW. slope.

31.80 Canyon, dense aspen in bottom, course N. 80° W.; asc. 40 ft. along W. slope.

37.00 Desc. 40 ft. along W. slope.

40.01 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 25 ins. in rock, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S35	S36
1940	

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Desc. 30 ft. along W. slope.

42.50 Wash, near head, course SW.; asc. 60 ft. along W. slope.