

. Dependent Resurvey of E. Bdy., T. 45 N., R. 65 E.

Chains

T46N R65E
 S36
 S 1 | S 6
 R65E | R66E
 T45N
 CC
 1940

The standard cor. of Ts. 46 N., Rs. 65 and 66 E., heretofore described, bears S. 89° 39' E., 31.78 chs. dist.

Land, rolling mountainous.

Soil, gravelly; 3d rate.

Timber, none.

Undergrowth, sagebrush.

Grazing, fairly good.

Dependent Resurvey of the S. Bdy., T. 45 N., R. 65 E.

Reestablishment of the survey executed by Deputy Surveyors Monroe and McClellan in 1881.

From the cor. of Ts. 44 and 45 N., Rs. 65 and 66 E.

N. 89° 41' W., bet. secs. 1 and 36 along the S. bdy. T. 45 N., R. 65 E.

Over rolling land, through very scattering juniper timber.

12.50 Leave, scattering timber.

24.30 Wash, course N.; asc. 130 ft. over E. slope.

32.00 Enter scattering juniper timber.

40.31 The $\frac{1}{4}$ sec. cor., a sandstone 18x12x5 ins., set 3 ins. in the ground and in a mound of stone, and mkd. $\frac{1}{4}$ on E. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the original mkd. stone deposited at base for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 36
 $\frac{1}{4}$ ———
 S 1
 1940

from which

A juniper, 15 ins. diam., bears S. 13 $\frac{1}{2}$ ° E., 114 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A juniper, 14 ins. diam., bears N. 2 $\frac{1}{2}$ ° W., 199 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

Corner is located on a ridge bearing N. and S.

N. 89° 25' W., bet. secs. 36 and 1. (W. $\frac{1}{2}$ mile)

Desc. 125 ft. over W. slope.

10.00 Wash, course SW.; asc. 80 ft. over E. slope.

20.00 Ridge bears N. 30° E. and S.; desc. 190 ft. over W. slope.

28.90 Road, bears N. and S. across valley.