

Dependent Resurvey of the Ninth Standard Parallel North, along the South Boundary of T. 46 N., R. 67 E.

Chains

Resurvey commenced at the original standard corner of T. 46 N., Rs. 67 and 68 E., a juniper post, 3 ins. square, 2½ ft. long, fallen beside a mound of earth and mkd. XLVIN RLXVIII XXXI on one face, 6 notches on one edge and RLXVII XXXVI SC on another face.

At point for corner

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, with the original post deposited at base and alongside, for standard cor. of T. 46 N., Rs. 67 and 68 E., with brass cap mkd.

SC  
T46N  
R67E R68E  
S36 | S31

1941

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence

S. 89° 58' W., along the S. bdy. of sec. 36.

Over rolling mountainous land through scattering juniper and pinion timber; desc. 50 ft.

20.50 Wash, course NE.; leave scattering timber; asc. 60 ft. over rolling land.

27.80 Telephone line, bears N. 10° E. and S. 10° W.

31.60 Graded road, bears N. 10° E. and S. 10° W.

40.56 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for standard ¼ sec. cor., with brass cap mkd.

SC  
¼ S36

1941

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

53.50 Crest of ascent, bears N. 30° E. and S. 30° W.; desc. 50 ft. over NW. slope through juniper timber.

67.00 Bottom of swale, draining N. 20° W.; asc. 70 ft. over general E. slope through scattering juniper timber.

80.00 Crest of ascent, bears N. and S.; desc. slightly to sec. cor.

81.12 The original standard cor. of secs. 35 and 36, a mound of stone, no marks visible on any stone.

At point for corner

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard cor. of secs. 35 and 36, with brass cap mkd.

SC  
T46N R67E  
S35 | S36

1941