Chains	
	N. 0° 12' W., bet. secs. 1 and 6.
	Over rolling land.
7.70	Dim road, bears NW. and SE.
27.20	Graded road, bears S. 30° W. and N. 5° E.
30.00	Desc. 50 ft. over N. slope.
40.65	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

¼
S1 | S6
1941

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

	Over rolling land.
49.00	Wash, course E.; asc. slightly along gradual E. slope.
60.60	Telephone line, bears N. 30° E. and S. 30° W.
81.85	Intersect Ninth Standard Parallel North, at the proportionate distance for the closing cor. of Ts. 45 N., Rs. 67 and 68 E.
	Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for closing cor. of T. 45 N., Rs. 67 and 68 E., with brass cap mkd.

T46N R67E
S36

S1 | S6
R67E | R68E
T45N
CC
1941

raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

From the closing township cor., the standard cor. of T. 46 N., Rs. 67 and 68 E., bears N. 89° 58' E., 38.28 chs. dist. and the ¼ sec. cor. of sec. 36 bears S. 89° 58' W. 2.28 chs. dist.
Land, rolling.
Soil, clay, gravelly and rocky; 4th rate.
Timber, some few scattered juniper.
Undergrowth, sagebrush.
Grazing, fair.

Dependent Resurvey of the Subdivision of
T. 45 N., R. 67 E.

Reestablishment of the surveys executed by Monroe and McClellan, Deputy Surveyors, in 1881.

Resurvey commenced at the corner of secs. 1, 2, 35 and 36, on the S. bdy. of the township.

Thence