Chains	
41.06	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.
	¼ S3 / S10 1942
	raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
42.00	Draw, drains N. 75° E.; asc. 200 ft. over rolling land.
65.00	Unimproved road, bears irregularly N. and S.
82.13	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, sandy clay and gravelly and rocky; 3rd and 4th rate. Timber, very little scattering juniper at extreme eastern part of mile. Undergrowth, sagebrush. Grazing, fairly good.
	N. 0° 58' E., bet. secs. 3 and 4.
	Over rolling land.
32.00	Draw, drains S. 60° E.
40.98	Proportionate distance.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with charcoal deposited at the base, for ¼ sec. cor., with brass cap mkd.
	¼ S4 | S3 1942
	No suitable accessory.
60.50	Draw, drains E.; asc. 100 ft. over S. slope.
81.00	Desc. 30 ft. along steep E. slope.
82.26	Intersect the Ninth Standard Parallel North.
	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for closing cor. of secs. 3 and 4, with brass cap mkd.
	T46N R67E S33 T45N | R67E S4 | S3 CC 1941
	From the closing cor., the standard cor. of secs. 33 and 34, bears N. 88° 48' E., 39.07 chs. dist. and the ¼ cor. of sec. 33 bears S. 88° 48' W. 1.77 chs. dist.
82.75	The original closing corner of secs. 3 and 4, a gray