

Dependent Resurvey of the Subdivision of  
T. 45 N., R. 67 E.

733

Chains 34.00	Wash, course generally SE.; asc. 100 ft.
41.13	Proportionate distance.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \frac{S4}{S9}$ 1942  raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.
	Across broad, flat spur, projects S. 60° E.
48.00	Unimproved road, bears N. 60° W. and S. 60° E., along crest of spur; desc. 30 ft. to wash.
55.80	Wash, course S. 60° E.; asc. 80 ft. to sec. cor.
70.00	Over rolling land.
82.27	The cor. of secs. 4, 5, 8 and 9.  Land, rolling. Soil, gravelly; 3rd rate. Timber, none. Undergrowth, sagebrush. Grazing, good.
	North, bet. secs. 4 and 5.  Over rolling land.
11.50	Draw, drains SE.
16.50	Unimproved road, bears SE. and NW.
20.50	Draw, drains S. 60° E.
26.00	Draw, drains SE.
40.57	Proportionate distance.  Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, with a granite stone, 3x4x5 ins., mkd. with a cross (X), deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.  $\frac{1}{4} \frac{S5}{S4}$ 1942
60.00	Draw, drains S. 60° E.
80.00	Draw, drains S. 70° E.
82.20	Intersect the Ninth Standard Parallel North.  At proportionate distance  Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.