

Dependent Resurvey of the Subdivision of
T. 45 N., R. 67 E.

Chains

From the cor. of secs. 5, 6, 7 and 8.

N. 1° 12' W., bet. secs. 5 and 6.

Asc. 70 ft. over rolling land.

1.60 Unimproved road, bears E. and W.

12.00 Desc. 75 ft. over rolling land.

22.00 Boulder Creek, trickle of water, course E.; asc. 90 ft. over rolling land.

28.00 Unimproved road, bears E. and W.

40.21 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground, to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S6} \mid \text{S5} \\ 1942 \end{array}$$

Desc. 50 ft. to draw.

46.50 Draw, drains N. 80° E.; over rolling land.

66.00 Wash, course S. 75° E.; asc. 50 ft. over rolling land.

74.50 Crest of ascent bears E. and W.; desc. 25 ft. to closing cor.

81.40 Intersect the Ninth Standard Parallel North.

At proportionate distance.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 5, and 6, with brass cap mkd.

$$\begin{array}{c} \text{T46N R67E} \\ \text{S31} \\ \hline \text{S6} \mid \text{S5} \\ \text{T45N R67E} \\ \text{CC} \\ 1941 \end{array}$$

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. raise a mound

From the closing cor., the standard cor. of secs. 31 and 32, bears S. 89° 31' E., 38.34 chs. dist. and the $\frac{1}{4}$ sec. cor. of sec. 31 bears N. 89° 31' W., 2.32 chs. dist.

Land, rolling and rolling hills.

Soil, gravelly and rocky; 3rd and 4th rate.

Timber, none.

Undergrowth, sagebrush and scattered servicebrush.

Grazing, good.