

089

2

West bdy. Fractional T. 9 $\frac{1}{2}$ N., R. 70 E.

Chains

T10N	
R70E	
S31	

1915

From point of intersection, the true point for the $\frac{1}{4}$ sec. cor., on the S. bdy. of sec. 31, T. 10 N., R. 70 E., bears East, 29.08 chs. dist. From the true point the witness $\frac{1}{4}$ sec. cor., bears West, 0.30 chs. dist., an iron post 1 in. diam., set and mkd. as described in the official record. The marks on the S. side were obliterated and the brass cap is now mkd.

$\frac{1}{4}$
S31
WC

1915

The marks "S6" were obliterated and the SE. bearing tree is now marked WC $\frac{1}{4}$ BT.

Land, rolling and hilly.
Soil, gravelly and rocky; 3rd and 4th rate.
Timber, very few scattered junipers.
Undergrowth, yellowtop and shadscale.
Grazing, fair.

Subdivision of Fractional T. 9 $\frac{1}{2}$ N., R. 70 E.

Beginning at the cor. of secs. 1, 2, 35 and 36, an iron post, 2 ins. diam., described in the field notes of the survey of the N. bdy. of T. 9 N., R. 70 E., executed under this group.

N. 0° 01' W., bet. secs. 35 and 36.

Over level land.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S35 S36

1915

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

55.60

Intersect the S. bdy. of T. 10 N., R. 70 E.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of fractional secs. 35 and 36, with brass cap mkd.

T10N R70E	
S36	
S35	
T9 $\frac{1}{2}$ N	
R70E	
CC	

1915

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.

From point of intersection, the $\frac{1}{4}$ sec. cor. on the S. bdy. of sec. 36, T. 10 N., R. 70 E., bears East, 31.20 chs. dist.; an iron post,