

Survey of the South Boundary of T. 14 N., R. 68 E.

Chains

A fir, 10 ins. diam., bears N. $45\frac{3}{4}^{\circ}$ W., 339 lks. dist., mkd. T 14 N R 68 E S 32 BT.

Land, mountainous.
Soil, rocky, sandy and gravelly; 4th rate.
Timber, Mahogany, pine, fir and aspen.
Undergrowth, sagebrush and a fair growth of grass.
Grazing, fair.

West, along the S. bdy. of sec. 32.

Desc. 450 ft. over mountainous land, through dense undergrowth, over a NW. slope.

18.60 Head of wash, course SW.; desc. 230 ft. over a S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 32

1940

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. raise a mound

Desc. 30 ft. over S. slope.

43.60 Same wash, 15 lks. wide, 1 ft. deep, course N. 75° W.; desc. 100 ft. along a W. slope.

53.90 Same wash, from N. 70° E.; course nearly W.; desc. along bottom of wash, 180 ft.

69.70 Leave wash, course SW.; asc. 10 ft. over SE. slope.

73.42 The original cor. of secs. 5, 6, 31, and 32, on the N. bdy. of T. 13 N., R. 68 E. heretofore described.

Land, mountainous.
Soil, sandy, gravelly and rocky; 4th rate.
Timber, scattering juniper.
Undergrowth, Sagebrush, and a fair growth of grass.
Grazing, fair.

Dependent Resurvey of the North Boundary of sec. 6, T. 13 N., R. 68 E.

Reestablishment of survey executed by E.B. Monroe and A.G. Bateman, Deputy Surveyors, in 1871.

Begin at the original cor. of secs. 5, 6, 31, and 32, on the N. bdy. of T. 13 N., R. 68 E. This original cor. can not serve as a cor. for the subdivision of T. 14 N., R. 68 E. Therefore change this original cor., which will refer only to secs. 5 and 6, T. 13 N., R. 68 E.

At point for cor., with the original stone deposited at base.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 5 and 6, T. 13 N., R. 68 E, with brass cap mkd.