

Subdivision of T. 14 N., R. 68 E.

Chains

West, on true line bet. secs. 7 and 18.

Desc. 360 ft. over a broken W. slope of mountainous land, through scattering timber and dense undergrowth.

14.00 Ravine, course N. 15° W. about 12.00 chs. dist.; thence NW.; asc. 70 ft.

21.00 Top of spur, projects N. 10° W. about 10.00 chs. dist., thence NW.; desc. 115 ft.

29.00 Head of wash, course NW.; desc. 30 ft.

34.00 Top of spur, projects N. 70° W.; desc. 30 ft.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 7
 $\frac{1}{4}$
S 18
1940

from which

A pinon pine, 6 ins. diam., bears S. 20 $\frac{1}{2}$ ° W., 31 lks. dist., mkd. $\frac{1}{4}$ S 18 BT.

A pinon pine, 10 ins. diam., bears N. 38° W., 128 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.

Desc. 245 ft. over SW. slope.

52.00 Head of wash, course S. 80° W.; desc. 160 ft.

60.00 Ditch, course NW.; desc. 90 ft.

64.20 Ravine, (local name " Dry Gulch"), channel 40 lks. wide, 4 ft. deep, course N. 15° W.; asc. 190 ft. over NE. slope. Road, in bottom of Dry Gulch.

73.00 Top of spur, projects N. 30° W.; desc. 90 ft.

76.00 Ravine, course N.; asc. 5 ft.

76.83 Intersect the E. bdy. of T. 14 N., R. 67 E.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, for closing cor. of secs. 7 and 18, with brass cap mkd.

T14N | T14N
R67E | S 7 CC
S13 | S18
R68E
1940

from which

The reestablished cor. of secs. 12 and 13, T. 14 N., R. 67 E., bears N. 0° 20' W., 4.14 chs. dist.

A pinon pine, 9 ins. diam., bears N. 71 $\frac{3}{4}$ ° E., 105 lks. dist.; mkd. T 14 N R 68 E S 7 CC BT.

A pinon pine, 10 ins. diam., bears S. 68 $\frac{3}{4}$ ° E.; 93 lks. dist., mkd. T 14 N R 68 E S 18 CC BT.